

DAVIS-HOWLAND OIL CORPORATION -- PETROLEUM ELECTRICAL INSULATING OIL --  
9160-00-075-9816

===== Product Identification =====

Product ID:PETROLEUM ELECTRICAL INSULATING OIL

MSDS Date:10/24/1988

FSC:9160

NIIN:00-075-9816

MSDS Number: BLJFB

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-4

73-6651

Emergency Phone Num:716-473-6651

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT

NAPHTHENIC  
CAS:64742-53-6  
RTECS #:PY8036000  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:5 MG/M3 (OIL MIST)

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE CONTACT MAY CAUSE IRRITATION. IF  
MATERIAL IS ASPERATED INTO THE LUNGS, MILD TO SEVERE PULMONARY  
INFURY AND POSSIBLY DEATH MAY RESULT.  
Effects of Ove  
rexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE  
SKIN IRRITATION.  
Medical Cond Aggravated by Exposure:NONE RECOGNIZED.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MIN. OR UNTIL IRRITATION  
SUBSIDES. SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN  
THOROUGHLY WITH SOAP AND WATER. INHALATION: NOT NORMALLY A  
PROBLEM. INGES TION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN  
IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:293F,145C  
Autoignition Temp:Autoignition Temp Text:>399F  
Extinguishing Media:FOAM, WATER SPRAY, DDRY CHEMICAL, CARBON DIOXIDE  
AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.  
Fire Fighting Procedures:USE WATER TO KEEP CONTAINERS COOL. USE  
SUPPLIED-AIR BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES OR  
AS OTHERWISE INDICATED.  
Unusual Fire/Explosion Hazard:HAZARDOUS MATERIALS MAY BE FORMED  
UPON  
INCOMPLETE COMBUSTION.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER  
SUITABLE ABSORBENT RO SPILL AREA. MINIMIZE SKIN CONTACT. KEEP  
PRODUCT OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING.  
Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS AND STORAGE CONTAINERS  
CLOSED WHEN NOT IN USE

. DO NOT STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES, IF NEEDED.

Ventilation:USE LOCAL EXHAUST TO CAPTURE VAPOR, MISTS OR FUMES.

Protective Gloves:CHEMICAL-RESISTANT GLOVES.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:CHEMICAL-RESISTANT APRON OR OTHER IMPERVIOUS CLO

THING, IF NEEDED.

Work Hygienic Practices:USE NORMAL PRACTICES WHEN HANDLING CHEMICALS.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:460F,238C

Vapor Pres:5

Spec Gravity:0.88

Viscosity:55 SSU

Evaporation Rate & Reference: