

TRADCO CHEMICAL CORP -- ISOPROPANOL, ANHYDROUS -- 6810-00-286-5435

=====
Product Identification
=====

Product ID:ISOPROPANOL, ANHYDROUS

MSDS Date:05/15/1989

FSC:6810

NIIN:00-286-5435

MSDS Number: BLJHL

=== Responsible Party ===

Company Name:TRADCO CHEMICAL CORP

Address:1081 ROSEMARY BLVD

City:AKRON

State:OH

ZIP:44306-3727

Country:US

Emergency Phone Num:NONE

Preparer's Name:DGSC/SSH

CAGE:LO179

===

Contractor Identification ===

Company Name:TRADCO CHEMICAL CORP

Address:1081 ROSEMARY BLVD

Box:City:AKRON

State:OH

ZIP:44306-3727

Country:US

CAGE:LO179

Company Name:TRADECO CHEMICAL CORP

Address:1081 ROSEMARY BLVD

Box:City:AKRON

State:OH

ZIP:44306-3727

Country:US

CAGE:65248

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 100%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

==

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 5840 MG/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: OVEREXPOSURE MAY LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION, LEADING TO HEADACHES AND DIZZINESS. EYE: MAY LEAD TO IRRITATION AND WILL INJURE EYE TISSUE IF NOT REMOVED PROMPTLY. SKIN: MAY LEAD TO DERMATITIS. INGESTION: MAY

LEAD TO VOMITING. CHRONIC: PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:THIS CHEMICAL IS NOT LISTED AS HAVING ANY EVIDENCE OF BEING CARCINOGENIC.

Effects of Overexposure:OVEREXPOSURE MAY LEAD TO DIZZINESS, HEADACHES, DERMATITIS AND EYE IRRITATION. HIGH VAPOR CONCENTRATIONS ARE ANESTHETIC AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure:PERSONS WITH SKIN, HEART, RESPIRATORY, OR ANY OTHER MEDICAL CONDITION SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:SKIN: IMMEDIATELY FLUSH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF NECESSARY. INHALATION: IMMEDIATELY REMOVE VICTIUM TO FRESH AIR. GIVE CPR IF BREATHING IS STOPPED. GE T MEDICAL ATTENTION. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: GET PROMPT MEDICAL ATTENTION. KEEP AT REST. GIVE TWO GLASSES OF WATER AND INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:53.0F,11.7C

Lower Limits:2.0

Upper Limits:12.7

Extinguishing Media:ALCOHOL-TYPE OR ALL-PURPOSE FOAMS BY MANUF. RECOMMENDED TECHNIQUES FOR LRG. FIRES. USE CO2 OR DRY CHEM. FOR SMALL FIRES.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WAT

ER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL AND BE IGNITED BY PILOT LIGHTS, FLAMES, SPARKS, HEATERS, ETC. AT DISTANCES FROM THE HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF LEAK

S. REMOVE LIQUID BY VACUUM OR ABSORBENT. FLUSH RESIDUE WITHWATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED WORK AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. FLAMMABLE LIQUID; EMPTY CONTAINERS CAN CONTAIN LIQUID/VAPOR RESIDUE.

Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXOPSE SUCH CONTAINERS TO HEAT, FLA ME, SPARKS, STATIC

ELECTRICITY, OR OTHER SOURCES OF IGNITION. EXPLOSION HAZARD. EMPTY DRUMS SHOULD BE C COMPLETELY DRAINED, BUNGED & DISPOSED OF.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:BUTY L RUBBER

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:SAFETY SHOES, EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health NONE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:180F,82C

Vapor Pres:33

Vapor Density:2.07

Spec Gravity:0.7864

Evaporation Rate & Reference:2.88 (BUTYL ACETATE=1)

Solubility

in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, CHARACTERISTIC ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CONCENTRATED NITRIC AND SULFURIC ACIDS, STRONG OXIDIZERS, ALDEHYDES,
HALOGENS, AND HALOGEN COMPOUNDS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:BURNING MAY PRODUCE CARBON MONOXIDE
AND OR CARBON DIOXIDE.

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ALL WASTE IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability

for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.