

N/P -- SOLDER SEAL LIQUID WRENCH NO.1 (AEROSOL -- 6850-00-508-0076

Product ID:SOLDER SEAL LIQUID WRENCH NO.1 (AEROSOL

MSDS Date:01/01/1987

FSC:6850

NIIN:00-508-0076

MSDS Number: BLJHY

=== Responsible Party ===

CAGE:77628

=== Contractor Identification ===

Company Name:RADIATOR SPECIALTY COMPANY

Address:1900 WILKINSON BLVD.

Box:34689

City:CHARLOTTE

State:NC

ZIP:28208

Country:US

Phone:704-377-6555/303-623-5716

CAGE:77628

=====

== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 89-90%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM (AIR)

Ingred Name:PETROLEUM MINERAL OIL

CAS:64742-06-9

Fraction by Wt: 8-9%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:5 MG/M3 (MIST)

Ingred Name:CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000

Fraction by Wt: 2-3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;9

=====
 ===== Hazards Identification =====
 =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYE: IRRITANT. INHALATION: EXCESSIVE
 INHALATION CAN CAUSE DIZZINESS, RESPIRATORY AND LUNG IRRITATION.
 SKIN CONTACT: IRRITANT. PROLONGED EXPOSURE CAN CAUSE DERMATITIS.
 INGESTION: HARMFUL OR FATAL IF SW ALLOWED. CAN CAUSE GASTRIC
 DISTURBANCE,NAUSEA. ASPIRATION CAN LEAD TO LUNG IRRITATION.

=====
 ===== First A
 id Measures =====
 =====

First Aid:EYE: FLUSH W/WATER--15 MINUTES, WHILE LIFTING EYELIDS.
 ADVERSE EFFECTS PERSIST--GET MED AID. SKIN: WASH W/SOAP & WATER.
 REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE RE-USE. INHALATION:
 REMOVE TO FRES H AIR. DIFFICULT BREATHING--ADMINISTER OXYGEN.
 BREATHING STOPPED--ARTIFICIAL RESPIRATION. GET MED AID. INGESTION:
 DO NOT INDUCE VOMITING. GET MED AID. DO NOT ADMINISTER EPINEPHRINE
 OR ADRENALIN.

=====
 ===== Fire Fig
 hting Measures =====
 =====

Flash Point:NR

=====
 ===== Accidental Release Measures =====
 =====

Spill Release Procedures:OBSERVING HEALTH HAZARDS DESCRIBED ABOVE,
 REMOVE IGNITION SOURCES, VENTILATE AREA. CONFINE
 SPILL.SELF-CONTAINED BREATHING APPARATUSSTE DRUM.

=====
 ===== Handling and Storage =====
 =====

Handling and Storage Precautions:KEEP AWAY FROM IGNITION SOURCE AND
 OXIDIZERS. STORE IN A COOL PLACE.

Other Precautions:WEARING
 CONTACT LENSES IS INADVISABLE. DO NOT
 PUNCTURE OR INCINERATE CONTAINERS. KEEP AWAY FROM CHILDREN AND
 ANIMALS.

=====
 ===== Exposure Controls/Personal Protection =====
 =====

Respiratory Protection:USE NIOSH APPROVED SELF-CONTAINED BREATHING
 RESPIRATOR.

Ventilation:USE WITH ADEQUATE GENERAL/VENTILATION.

Protective Gloves:SOLVENT-RESISTANT GLOVES

Eye Protection:FULLY PROTECTIVE GOGGLES/FACE SHIELD

Other Protective Equipment:SOLVENT-RESISTANT APRON.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

===== Stability and Reactivity Data =====

Hazardous Decomposition Products:FIRE: NORMAL PRODUCTS OF COMBUSTION:
SMOKE, CARBON DIOXIDE, CARBON MONOXIDE, SULFUR TRIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
GOVERNMENT LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.