View NSN Online: https://aerobasegroup.kr/nsn/8010-00-584-3011

BAKER SEALANTS & COATINGS CO., INC. -- EXTERIOR PAINT, MED COLORS, P-81T 8010-00-584-3011

Product ID: EXTERIOR PAINT, MED COLORS, P-81T MSDS Date:11/07/1990 FSC:8010 NIIN:00-584-3011 MSDS Number: BLJJM === Responsible Party === Company Name: BAKER SEALANTS & COATINGS CO., INC. Address:234 SUYDAM AVE Box:8 City: JERSEY CITY State:NJ ZIP:07304-3306 Country:US Info Phone Num:201-333-6986, FAX-201-333-6955 Emergency Phone Num:201-333-6986, CHEMTREC-800-356-3129 Preparer's Name: CHARLES FRIEDMAN, TECH DIR CAGE:FO833 === Contractor Identification === Company Name: BAKER SEALANTS & COATINGS CO., INC. Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Phone:(201) 333-6986 CAGE:FO833 Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094

=======

===== Composition/Information on Ingredients ==========

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 7% Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:EXTENDERS & COLORS CAS:1317-65-3 Fraction by Wt: 24% Other REC Limits:NONE SPECIFIED

Ing red Name:LINSEED OIL CAS:8001-26-1 RTECS #:OI9690000 Fraction by Wt: 20% Other REC Limits:NONE SPECIFIED

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 13% Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

Ingred Name:ALKYD RESIN Fraction by Wt: 25% Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 250 RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inh

alation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION:IN EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF DIGESTIVE TRACT & SIGNS OF NERVOUS SYSTEM DEPRESSION (E.G., DROWSINESS, DIZZINESS, LOSS OF COORDINATION & FATIGUE). ASPIRATION HAZARD-INFLAMMA TION & POSSIBLE SEVERE LUNG DAMAGE.

Effects of Overexposure:EYES:DIRECT CONTACT WITH VAPORS/MIST MAY CAUSE STINGING, TEARING, REDNESS. PROLONGED/REPEATED SKIN

CONTACT:REDNESS,BURNING,DRY,CRACKING. NONE KNOWN FOR SKIN ABSORPTION. INHALE:IN HIGH CONCENTRATIONS MAY CAUSE IRRIT OF NOSE, THROAT & SIGNS OFNERVOUS SYSTEM DEPRESSION (E.G., DROWSI, DIZZI, LOSS OF COORDINATION & FATIGUE)

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO EFFECTS. RESPIRATORY SYMPTOMS ASSOCIATED WITH PRE-EXISTING LUNG DISORDERS (E.G., ASTHMA-LIKE CONDITIONS).

First Aid:CALL L.A. POISON INFO CENTER(24 HRS.)(800)356-3129 THEN CALL DOCTOR. EYES:FLUSH W/WATER FOR 15 MIN. SKIN:REMOVE CONTAM CLOTHES,WASH W/SOAP & WATER THORO. IF IRRIT/RED,SEEK MED. INHALE:MOVE TO FRESH AI R.IF NOT BREATHING,GIVE CPR.IF BREATHING DIFF,ADMIN OXYGEN.INGEST:DO NOT INDUCE VOMIT/GIVE ANYTHING BY WAY OF MOUTH. IF DROWSY/UNCONSC PLACE ON LEFT SIDE W/HEAD DOWN, DO NOT LEAVE UNATTEND IF POSSIBLE

=================== Fire Fighting Measures

Flash Point Method:TCC Flash Point:>105F,>41C Lower Limits:5 Upper Limits:0.8 Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL, CO2 OR FOAM. Fire Fighting Procedures:USE SCBA. WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS & COOLING CONTAINERS EXPOSED TO HEAT & FLAME. AVOID SPREADING BURNING LIQUID W/WATER USED FOR COOLING. Unusual Fire/Explosion Hazard:THIS MATERIAL IS COMBUSTIBLE & MAY BE IGNITED BY HEAT OR FLAME. THIS MATERIAL WILL BURN, BUT WILL NOT IGN ITE READILY.

Spill Release Procedures:LG:STAY UPWIND AWAY FROM SPILL. KEEP ALL SOURCES OF IGNITE AWAY. VENT AREA. KEEP OUT OF DRAINS,SEWERS,WATERWAYS. USE SAND, OTHER INERT MATERIAL TO DAM & CONTAIN. DO NOT FLUSH AREA W/WATER. SM:USE ABSO RB PADS. CONTACT FIRE AUTHORITIES & APPROPRIATE * Neutralizing Agent:N/K.

Handling and Storage Precaution s:KEEP CONTAIN TIGHTLY

CLOSED,COOL,DRY,AWAY FROM IGNITE SOURCES. USE & STORE W/ADEQUATE VENT. EMPTY CONTAIN RETAIN RESIDUE MAY EXPLODE CAUSING INJURY** Other Precautions:**OR DEATH, EMPTY DRUMS SHOULD BE COMPLETELY DRAINED. PROPERLY BUNGED & PROMPTLY SHIPPED TO SUPPLIER OR DRUM RECONDITIONER. ALL OTHERS DISPOSE IN ENVIRONMENT SAFE MANNER & IN ACCORD W/GOVERN PRODUCT, REFER TO OCCUP SAFETY/HEALTH ADMIN REGS

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: ADVISED WHEN CONCENTRATIONS EXCEED ESTABLISHED EXPOSURE LIMITS. DEPENDING ON AIRBORNE CONCENTRATION, USE RESPIRATOR OR GAS MASK WITH APPROPRIATE CARTRIDGE & CANNISTERS (NIOSH APPROVED, IF AVAILABLE) OR SUPPLIED AIR EQUIPMENT. Ventilation: ADDITIONAL VENTILATION/EXHAUST SYSTEM MAY BE REQUIRED. WHERE EXPLOSIVE MIX MAY BE PRESENT, USE SYSTEMS SAFE FOR LOCATION Protective Gloves: IMPERMEABLE TO SPECIFIC MATERIAL HANDLED Eye Protection: APPROVED EYE PROTECTION Oth er Protective Equipment: EQUIPMENT TO AVOID INHALATION OF VAPORS &

PERSONAL CONTACT WITH PRODUCTS.

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE PRACTICES. Supplemental Safety and Health

Boiling Pt:B.P. Text:315 TO 395F Vapor Pres:3.0 @ 68F Vapor Density:3.9 Spec Gravity:1.31 Viscosity:75-80 K.U. Evaporation Rate & amp; Reference:.13 (BU AC=1) Solubility in Water:INSOLUBLE Appearance and Odor:PAINT, THINNER Percent Vola tiles by Volume:23

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR BASES, OXIDIZING AGENTS & SELECTED AMINES. Hazardous Decomposition Products:COMBUSTION MAY YIELD CARBON MONOXIDE &/OR CARBON DIOXIDE.

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE & FEDERAL REGULATIONS. * FEDERAL, STATE OR LOCAL AGENC

IES. (HIGHWAY OR RAILWAY SPILLS: CALL CHEMTREC (800) 424-9300 CONT. U.S. (COLLECT) (202) 483-7616 FROM ALASKA & HAWAII)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.