

NONFLUID OIL CORP -- G-60/EPV -- 9150-00-929-7946

===== Product Identification =====

Product ID:G-60/EPV
MSDS Date:03/16/1992
FSC:9150
NIIN:00-929-7946
MSDS Number: BLJLG
=== Responsible Party ===
Company Name:NONFLUID OIL CORP
Address:298 DELANCY ST
City:NEWARK
State:NJ
ZIP:07105-3009
Country:US
Info Phone Num:201-344-3451
Emergency Phone Num:201-344-3451
CAGE:76736

=== Contractor Identification

===
Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC
Address:298 DELANCY ST
City:NEWARK
State:NJ
ZIP:07105-3009
Country:US
Phone:201-344-3451/800-424-9300(CHEMTREC)
CAGE:76736

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL BASE STOCK
CAS:64791-97-5
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:10 MG/M3 (STEL) MIST

Ingred Name:HYDROTREATED HEAVY NAPHTHENIC DISTILLATE, PETROLEUM
CAS:64742-52-5
RTECS #:PY8035000
Other

REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:10 MG/M3 (STEL) MIST

Ingred Name:SOLVENT,DEWAXED RESIDUAL OIL (PETROLEUM)
CAS:64742-62-7
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:10 MG/M3 (STEL) MIST

Ingred Name:LUBRICATING OIL BASE STOCK
CAS:15890-25-2
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:10 MG/M3 (STEL) MIST

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:Y
ES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT
TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN IRRITATION . EXPOSURE
TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION. NO KNOWN
ADVERSE CHRONIC EFFECTS.
Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS MEMBRANE.
Medical Cond Aggravated by Exposure:THIS PRODUCT, LIKE ANY OTHER
CHEMICALS, MAY ENHANCE ALLERGIC CONDITION ON CERTAIN PE
OPLE.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION
PERSISTS GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND
WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DO NOT INDUCE
VOMITING. GIVE WATER AND GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:375F,191C
Lower Limits:1%BASE FLUID
Upper Limits:6% BASEFLUID
Exti

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG.
(USE MEDIA CAREFULLY TO PREVENT FROTHING.)

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES. RECOVER
FREE PRODUCT. AD

D ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA.

SWEEP OR SCRAPE UP MATERIAL AND COLLECT FOR PROPER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. USE METHODS
ADVOCATED FOR PETROLEUM PRODUCTS. DO NOT STORE OR MIX WITH
OXIDIZING MATERIALS. AVOID EXCESSIVE HEAT OR FLAMES.

Other Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH
E

YES AND INHALATION OF FUMES, VAPORS OR MISTS. DO NOT INGEST. WASH
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. RECOMMENDED IF FUMING OR
MISTING.

Ventilation:MECHANICAL (GENERAL) RECOMMENDED IF FUMING OR MISTING.

Protective Gloves:FOR PROLONGED OR FREQUENT CONTACT.

Eye Protection:RECOMMENDED IF SPLASHING OR MISTING.

Other Protective Equipment:NORMALLY NOT REQUIRED. PROVIDE EYE WASH
STATIO

N AND SAFETY SHOWER.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Melt/Freeze Pt:M.P/F.P Text:385F,196C

Vapor Pres:10

Spec Gravity:0.90

Evaporation Rate & Reference: