

CLIFTON ADHESIVE INC -- FA-1005 ACCELERATOR -- 8040-00-266-7427

=====
Product Identification
=====

Product ID:FA-1005 ACCELERATOR

MSDS Date:03/25/1990

FSC:8040

NIIN:00-266-7427

Kit Part:Y

MSDS Number: BLJTC

=== Responsible Party ===

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

City:WAYNE

State:NJ

ZIP:07470

Country:US

Info Phone Num:201-694-0845

Emergency Phone Num:201-694-0845/800-424-930

0 CHEMTREC

CAGE:79833

=== Contractor Identification ===

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ

ZIP:07470

Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 85%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TRADE SECRET

REGISTRY #(1397250002)-5067 P
Other REC Limits:NONE SPECIFIED

Ingred Name:ABOVE EXPOS LIM ARE FOR AIR LEVELS ONLY. WHEN SKIN CNTCT
OCCURS, OVEREXPOS MAY RESULT THOUGH AIR LEVELS ARE < ABOVE LIMS
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: NAUSEA AND/OR NARCOSIS.
Effe
cts of Overexposure:IRRITATION TO EYES AND MUCOUS MEMBRANES. CAN
ALSO CAUSE SKIN DRYNESS.
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS. TARGET
ORGANS: CONTAINS TOLUOL WHICH BASED ON ANIMAL DATA MAY CAUSE LIVER
ABNORMALITIES, KIDNEY, LUNG & SPLEEN DAMAGE. IN HUMANS, LIVER
ABNORMALITIES.

=====
===== First Aid Measures =====

First Aid:UTILIZE THE SUGGESTED METHODS BELOW. IN EMERGENCY SITUATIONS,
NOTIFY A PHYSICIAN IMMEDIATELY. SKIN:
WASH W/SOAP & WATER. GET
MEDICAL ATTENTION. EYES: FLUSH EYES ABUNDENTLY W/CLEAN WATER AND
REFER TO P HYSICIAN. INGESTION: DO NOT INDUCE VOMITING. REFER TO
PHYSICIAN. EXCESSIVE INHALATION: REMOVE PATIENT TO FRESH AIR OR
GIVE OXYGEN. USE CPR IF PATIENT IS NOT BREATHING. REFER TO
PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:40.0F,4.4C
Autoignition Temp:Autoignition Temp Text:947 F
Lower Limits:1.3
Upper Limit
s:7.0
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA SHOULD BE WORN. USE
WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND DISPERSE VAPOR
CLOUD IF FIRE IS NOT PRESENT.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL
CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASHBACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL IN SAND, EARTH, VERMICULITE,
OIL

-DRI OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN APPROVED SOLVENT STORAGE AREA. KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT, OPEN FLAMES, SPARKS, HOT SURFACES AND OXIDIZING AGENTS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH-APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE LEVELS BELOW RECOMMENDED LIMITS.

Ventilation:LOCAL: REMOVE VAPORS DURING PROCESSING. MECHANICAL: EXPLOS-PROOF EQUIP. SPECIAL: REDUCE VAPOR CONC BELOW SPECIFIED LIM.

Protective Gloves:PVA GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:KEEP AREA CLEAN. CLEAN UP SPILLS IMMEDIATELY. PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:230F,110C

Vapor Pres:22 MM HG

Vapor Density:3.2

Spec Gravity:0.889

Appearance and Odor:REDDISH-BROWN, RUBBERY ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES AND OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON, ZINC, AND S

ULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.