

BAKER SEALANTS AND COATINGS CO -- NON-HARDING GASKET CEMENT -- 8030-00-291-1787

=====
Product Identification
=====

Product ID:NON-HARDING GASKET CEMENT

MSDS Date:12/03/1990

FSC:8030

NIIN:00-291-1787

MSDS Number: BLJTR

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Info Phone Num:201-333-6986 /

FAX 201-333-6955

Emergency Phone Num:201-333-6986

Preparer's Name:CHARLES FRIEDMAN

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 11%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STE

L
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:ROSIN RESIN
CAS:8050-09-7
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED

Ingred Name:KAOLIN
CAS:1332-58-7
RTECS #:GF1670500
Fraction by Wt: 55%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:CASTOR OIL,
CAS:68127-84-8
Fraction by Wt: 17%
Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK
CAS:7440-44-0
RTECS #:FF5250000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3
TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:EYES: MAY CAUSE TEARING AND BURNING. SKIN:
SLIGHT REDNESS. INHALATION: CAUSES HEADACHES AND DIZZINESS.
INGESTION: CRAMPS AND BURNING IN ESOPHAGUS.
Medical Cond Aggravated by Exposure:ASTHMA

=====
===== First Aid Measures =====

=====

First Aid:EYES: WASH COPIOUSLY WITH WATER. SKIN: WASH WITH WATER.
INHALATION: REMOVE TO OPEN FRESH AIR. INGESTION: DO NOT INDUCE
VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:78.0F,25.6C
Lower Limits:2.0
Upper Limits:12.7
Extinguishing Media:WATER, CO2, AND DRY CHEMICAL. (MM HG) 68 F

===== Accidental Release Measures =====

Spill Release Procedures:LARGE: KEEP AWAY FROM OPEN FLAMES. CALL LOCAL
FIRE DEPARTMENT. SMALL: SOAK UP WITH WOOD CHIPS OR SAW DUST. USE
LOCAL WASTE DISPOSAL METHODS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPRATURE (35-85 F)
AWAY FROM HEAT AND OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MASK FOR ALCOHOL VAPORS.
Ventilation:USE ADEQUATE NATURAL VENTILATION.
Protective Gloves:USE GLOVES
VES
Eye Protection:USE GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:81 (IPA)
Vapor Pres:37 IPA
Vapor Density:>AIR
Spec Gravity:(H2O=1) 1.51
Evaporation Rate & Reference:(BUAC=1) 1.7
Solubility in Water:SLIGHTLY SOL.
Appearance and Odor:BLACK PASTE, ALCOHOL.
Percent Volatiles by Volume:22.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS

Hazardous Decomposition Products:MAY PRODUCE CARBON MONOXIDE WITH INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:AS PER LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.