View NSN Online: https://aerobasegroup.com/nsn/8030-00-631-8013

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3100 PART B -- 8030-00-631-8013

Product ID:CS 3100 PART B MSDS Date:03/16/1990 FSC:8030 NIIN:00-631-8013 Kit Part:Y MSDS Number: BLJWD === Responsible Party === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91353 Country:US Info Phone Num:818-982-1650 Emergenc y Phone Num:818-982-1650 CAGE:14439 === Contractor Identification === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:14439 Ingred Name:LEAD PEROXIDE * CAS:1309-60-0 RTECS #:OG0700000 Fraction by Wt: 64% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3 Ingred Name:LEAD OXIDE * CAS:1317-36-8 RTECS #

:OG1750000 Fraction by Wt: 6% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Ingred Name:*THE EXPOSURE LIMITS ARE BASED ON PARTICLES..IN THIS PRODUCT THE LEAD DIOXIDE/OXIDE PARTICLES ARE WETTED OUT THEREFORE** RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Ingred Name:**THEREFORE AIRBORNE PARTICLES WILL NOT RESULT FROM NORMAL USE. RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes

of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: WEAKNESS, STUPOR. CHRONIC: KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS. Effects of Overexposure:HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR DYSFUNCTION.

Medical Cond Aggravated by Exposure: ANEMIA, KIDNEY DISEASE, PREGNANCY.

First Aid:INGESTION: INDUCE VOMITING, CONSULT A PHYSIC IAN AT ONCE. EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER AND CONTACT PHYSICIAN.

Flash Point Method:TCC
Flash Point:200F,93C
Extinguishing Media:FOAM, DRY CHEMICAL CO2, WATER.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE-PIECE, IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT WITH OXIDIZABLE MATERIAL AT HIGH TEMPERATURES OCCURS.

Spill Release Procedures: SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

Handling and Storage Precautions:STORE IN COOL DRY AREA. KEEP CONTAINERS CLOSED.

Respiratory Protection: IF SOOT IS FORMED USE NIOSH APPROVED RESPIRATOR. Ventilation: LOCAL EXHAUST--AIR HOOD; MECHANICAL--FAN Protective Gloves: RUBBER GLO VES Eye Protection: SAFETY GLASSES Other Protective Equipment: APPROPRIATE TO AVOID PROLONGED CONTACT. Work Hygienic Practices: TRAIN PERSONNEL IN THE SAFE HANDLING OF THIS PRODUCT. WASH HAND BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health

HCC:V5

Boiling Pt:B.P. Text:644F,340C Melt/Freeze Pt:M.P/F.P Text:LIQUID AT* Vapor Pres:NIL Vapor Density:*ROOM TEMP Spec Gravity:3.00 Evaporation Rate & amp; Reference:N IL Solubility in Water:NEGLIBIBLE Appearance and Odor:BROWN PASTE; OILY ODOR.

Stability Indicator/Materials to Avoid:YES OXIDIZABLE MATERIALS. Stability Condition to Avoid:HIGH HEAT. Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH BASE AND DISPOSE ACCORDING TO FEDERAL,

STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.