

TACC INTERNATIONAL CORP. -- CONTACT CEMENT -- 8040-00-779-9595

=====
Product Identification
=====

Product ID:CONTACT CEMENT

MSDS Date:08/01/1989

FSC:8040

NIIN:00-779-9595

MSDS Number: BLJWY

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878-7015

Emergency Phone Num:800-424-9

300 CHEMTREC

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 42-50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA II

I)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15-18%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES
Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: HEADACHE, DIZZINESS, NAUSEA,
UPPER RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL
DEPRESSION OR NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC: COULD
LEAD TO PERMANENT EFFECTS TO THE NERVOUS SYSTEM, BODY ORGANS OR
THE BRAIN. USE WITH ADEQUATE VENTILATION. EYES: IRRITATION. SKIN:
REMOVAL OF SKIN OILS, *
Effects of Overexposure:*IRRITATION, DERMATITIS, EVEN SENSITIZAT
ION
WITH LONG OVEREXPOSURE. INGESTION: MAY BE HARMFUL OR FATAL IF
SWALLOWED.

=====
First Aid Measures
=====

First Aid:INHALATION: GET FRESH AIR. EYES: FLUSH WITH WATER FOR AT
LEAST FIFTEEN MINUTES, IF NECESSARY, CALL A PHYSICIAN. SKIN: WASH
WITH SOAP AND WATER, IF NECESSARY, CALL A PHYSICIAN. APPLY A MILD
SKIN CREAM. INGESTION: CALL POISON CENTER IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash

Point Method:CC

Flash Point:1 (BUTYL ACETATE = 1)

Solubility in Water:NIL

Appearance and Odor:KETONE ODOR/CLEAR

Percent Volatiles by Volume:80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY.

Hazardous Decomposition Products:CO AND CO2.

===== Disposal Considerations =====

Waste Disposal Methods:

LIQUID MATERIAL IS DESIGNATED AS HAZARDOUS WASTE

UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.