

BORNE CHEMICAL CO INC -- OIL,ENGINE -- 9150-00-116-0506

=====  
Product Identification  
=====

Product ID:OIL,ENGINE

MSDS Date:12/10/1991

FSC:9150

NIIN:00-116-0506

MSDS Number: BLKWC

=== Responsible Party ===

Company Name:BORNE CHEMICAL CO INC

Address:632 SOUTH FRONT ST

City:ELIZABETH

State:NJ

ZIP:07207

Country:US

Info Phone Num:OUT OF BUSINESS

Emergency Phone Num:OUT OF BUSINESS

Resp. Party Other MS

DS Num.:WARD'S AUTO PARTS, INC.

Preparer's Name:DGSC-SSH

CAGE:17425

=== Contractor Identification ===

Company Name:BORNE CHEMICAL CO INC

Address:632 SOUTH FRONT ST

Box:City:ELIZABETH

State:NJ

ZIP:07200

Country:US

Phone:201-351-1717

CAGE:17425

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL(NOT SPECIFIED)

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:OTHER COMPONENTS

Other REC Limits:NONE SPECIFIED

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-EYES/SKIN:MAY CAUSE IRRITATION.  
INGESTION: ASPIRATION HAZARD. INHALATION: IRRITATION IF OVERCOME BY  
VAPOR FROM HOT PRODUCT. MAY HAVE CNS EFFECTS. CHRONIC-MAY CAUSE  
DERMATITIS.  
Explanation of Carcinogenicity:AVOID CONTACT WITH USED OILS.  
Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY TRACT.  
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:  
WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR  
OXYGEN IF NEEDED. IF OVER-EXPOSED TO OIL MIST, REMOVE FROM FURTHER  
EXPOSURE UNTIL EXCESSIVE MIST OIL CONDITION SUBSIDES. INGESTION :  
DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point:>200F,>93C  
Extinguishing Media:FOAM, WATER SPRAY (FOG), DRY CHEMICAL, AND CARBON  
DIOXIDE  
Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS  
COOL. USE SUPPLIED AIR BREATHING EQUIPMENT FOR ENCLOSED/CONFINED  
AREAS.  
Unusual Fire/Explosion Hazard:IF SPILL HAS NOT IGNITED, USE WATER SPRAY  
TO DISPERSE VAPORS. DON'T PRESSURIZE/CUT/WELD/BRAZE/SOLDER OR  
EXPOSE CONTAINERS TO IGNITION SOURCES, THEY MAY EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER  
SUITABLE ABSORBENT MATERIAL TO SPILL. OPEN ALL WINDOWS & DOORS.  
AVOID BREATHING VAPORS. KEEP PRODUCT OUT OF SEWERS & WATERCOURSES  
BY DIKING OR IMPOUNDING .

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP STORAGE CONTAINERS CLOSED WHEN  
NOT IN USE. DON'T STORE

RE NEAR HEAT/SPARKS/FLAME/STRONG OXIDANTS.

DON'T ATTEMPT TO REMOVE RESIDUE FROM CONTAINERS.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE (LIQUID/VAPOR) & CAN BE DANGEROUS. DON'T PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO SOURCES OF IGNITION. THEY MAY EXPLODE & CAUSE INJURY/ DEATH. AVOID SKIN & EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY

C

CONDITIONS OF USE & W/ADEQUATE VENTILATION. WEAR A NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS IF MISTS OR VAPORS ARE PRESENT.

Ventilation:PROVIDE ADEQUATE VENTILATION TO KEEP