

DEFT INC CHEMICAL COATING DIV -- CAT, MIL-C-83286, 16473, 03GY049CAT -- 8010-00-181-8255
===== Product Identification =====

Product ID:CAT, MIL-C-83286, 16473, 03GY049CAT
MSDS Date:06/06/1991
FSC:8010
NIIN:00-181-8255
Kit Part:Y
MSDS Number: BLKWQ
=== Responsible Party ===
Company Name:DEFT INC CHEMICAL COATING DIV
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92714-6205
Country:US
Info Ph
one Num:714-474-0400
Emergency Phone Num:800-424-9300 CHEMTREC
Preparer's Name:NORM GAUL
CAGE:33461
=== Contractor Identification ===
Company Name:DEFT, INC.
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92614
Country:US
Phone:949-474-0400
CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE (VAPOR PRESSURE: 0 MM HG)*
CAS:28182-81-2
Fraction by Wt: 30%
Other REC Limits:NONE SPECIFIED

Ingred Name:*HEXAMETHYLENE DIISOCYANATE (

HDI) (CAS 822-06-0) FREE
MONOMER CONTENT LESS THAN 0.7% BASED ON RESIN SOLIDS AT TIME OF**
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:**MANUFACTURE. AFTER 3-6 MO STORAGE THE FREE MONOMER
CONTENT MAY RISE (MAX-1.6%). ACGIH HAS PROPOSED A TVL OF 0.005***
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:***PPM TWA IN THE NOTICE OF INTENDED CHANGES FOR 1987-88.
MOBAY RECOMMENDS A CEILING LEVEL OF 1.02 PPM.
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIE
D

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL-3-ETHOXYPROPIONATE (VAPO
R PRESSURE 0.7 MM HG)
CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 45%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 625 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

tes of Entry: Inhalation: YES Skin: YES Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: IRRITATING TO EYES/NOSE/THROAT.
INHALATION: HEADACHES/DIFFICULT BREATHING/LOSS OF CONSCIOUSNESS.
CHRONIC: PROLONGED CONTACT OR LARGE SINGLE DOSE CAN DEVELOP
ISOCYANATE SENSITIZATION WHICH WILL CAUSE REACTION IN LATER
EXPOSURE OF ISOCYANATE LEVELS BELOW TLV VALUE OF ISOCYANATE.
Effects of Overexposure: INHAL: IRRITATION OF RESPIRATORY TR
ACT/ NERVOUS
SYSTEM DEPRESSION: HEADACHE/DIZZINESS/STAGGERING/CONFUSION/
UNCONSCIOUSNESS/COMA. SKIN/EYE: IRRITATION:
SWELLING/REDNESS/RASH/TEARING/ STINGING/DRYING/DEFATTING/CRACKING.
INGESTION: IRRITATION, POSS CORROSION TO MOUTH/DIGESTIVE TRACT.
VOMITING CAN CAUSE CHEMICAL PNEUMONITIS
Medical Cond Aggravated by Exposure: ASTHMA AND ANY OTHER RESPIRATORY
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE
SENSITIZATION.

===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO NO RISK AREA. RESTORE BREATHING.
ASTHMA-LIKE SYMPTOMS MAY APPEAR IMMEDIATE/DELAYED. MED ATTEN. SKIN:
REMOVE CLOTHING. WASH W/ SOAP/WATER. WASH CONTAMINATED CLOTHING
BEFORE REUSE. EYES : FLUSH W/ WATER (LOW PRESSURE) 15 MINUTES LIFT
LIDS OCCASIONALLY. MED ATTEN. INGESTION: DO NOT INDUCE VOMITING. DO
NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. MED ATTEN.

===== Fire Fighting Measures =====

Flash Point Method: TCC
Flash Point: 24.0F, -4.4C
Lower Limits: 1
Extinguishing Media: FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL,
WATER FOG.
Fire Fighting Procedures: FULL EQUIP/SCBA/PROTEC CLOTH. H2O/COOL CLOSED
CONTAINERS/PREVENT PRESSURE BUILD-UP/AUTO IGNITION/EXPLOSION. HAZ/OTHER
VAPORS GENERATED BY COMBUSTION/THERM DECOMP.
Unusual Fire/Explosion Hazard: CONTAINERS CLOSED, MAY EXPLODE HIGH HEAT.
NO HEAT/SPARKS/ELEC EQUIPMENT/OPEN FLAME. HOT SURFACES-SPECIAL
PRECAUTIONS. OVER

REXPOSURE TO DECOMP PRODS HEALTH HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBANT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:BUILDINGS TO COMPLY WITH OSHA 1910.106. AVOID STORING NEAR

HIGH TEMPERATURES, FIRE, OPEN FLAMES, AND SPARK SOURCES. CLOSED CONTAINERS/WELL VENTILATED.

Other Precautions:NO LEAKAGE/PROLONGED BREATHING OF VAPORS/SPRAY MIST. OVEREXPOSURE-ALLERGIC REACTION. NO CONTACT SKIN/EYES. DO NOT INGEST. UNDERSTAND MANUFACTURERS SAFETY PRECAUTIONS. WASH BEFORE EATING/SMOKING/ USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RSPRTR RECOMM/APPROVE FOR USE IN ORGANIC VAPOR

ENVIRON (AIR PURIFY/FRESH AIR). OBSERVE OSHA REGS--RSPRTR USE. VENT TO KEEP EXPOSURE LEVELS < OSHA LIMITS. VAPOR PARTIC RSPRTR (TC23C--NIOSH/MSHA) IF VAP OR LEVELS BELOW 10 X EXPOSURE LIMITS.

Ventilation:KEEP AIRBORNE CONCENTRAIONS OF SOLVENT/HDI/POLYISOCYANATES