

PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIV. -- COATING, POLYURETHANE, AIRCRAFT GREEN, 3403 -- 8010-01-131-6255

=====  
===== Product Identification =====

Product ID:COATING, POLYURETHANE, AIRCRAFT GREEN, 3403

MSDS Date:08/20/1991

FSC:8010

NIIN:01-131-6255

Kit Part:Y

MSDS Number: BLLCT

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIV.

Box:2153

City:WICHITA

State:KS

ZI

P:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT:800-255-3924

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PROPYLEN

E GLYCOL /METHYL ETHER ACETATE (VAPOR PRESSURE 2 MM  
HG @ 20 C) (SOLVENT)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-8

8-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: AIR

Spec Gravity:1.4

pH:4-7

Viscosity:70-85 KU

Evap

Evaporation Rate & Reference: SLOWER THAN DIETHYL ETHER

Solubility in Water: SLIGHT

Appearance and Odor: LIQUID, SOLVENT ODOR

Percent Volatiles by Volume: 56

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: EXCESSIVE HEAT (>100 F) AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN EPA PERMITTED FACILITY. NO INCINERATION OF CLOSED CONTAINERS. OBSERVE PRECAUTIONS OF FLAMMABLE MATERIALS. CONTAMINATED ABSORBENT DISPOSED IN HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.