

HEXAGON ENTERPRISES INC -- MIL-L-23699D METREX TURBO OIL 21(O-13D-2) -- 9150-00-681-5999

=====  
Product Identification  
=====

Product ID:MIL-L-23699D METREX TURBO OIL 21(O-13D-2)  
MSDS Date:03/01/1991  
FSC:9150  
NIIN:00-681-5999  
MSDS Number: BLMTV  
=== Responsible Party ===  
Company Name:HEXAGON ENTERPRISES INC  
Address:60 MIDVALE RD  
City:MOUNTAIN LAKES  
State:NJ  
ZIP:07046  
Country:US  
Info Phone Num:201-263-2600  
3-2600  
Emergency Phone Num:201-263-2600, CHEMTREC 800-424-9300  
Preparer's Name:GEORGE ROBERTS  
CAGE:0BJL6  
=== Contractor Identification ===  
Company Name:HEXAGON ENTERPRISES INC  
Address:60 MIDVALE RD  
Box:City:MOUNTAIN LAKES  
State:NJ  
ZIP:07046  
Country:US  
Phone:201-263-2600, CHEMTREC 800-424-9300  
CAGE:0BJL6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPRIETARY MIXTURE  
Fraction by Wt: 100%  
Other REC Limits:5 MG/M3 OIL MIST

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-INGESTION:NON-TOXIC., MAY CAUSE NAUSEA, VOMITING., MINUTE AMOUNTS ASPIRATED INTO LUNGS MAY CAUSE PULMONARY INJURY AND EVEN DEATH. INHALATION OF MIST MAY CAUSE CHEMICAL PNEUMONITIS. EYE:MILD IRRITATION. SKIN:NO EFFECT.  
CHRONIC-NONE  
Effects of Overexposure:EYE-IRRITATION. INGESTION: NAUSEA, VOMITING AND

DIARRHEA.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH EXISTING SKIN DISEASES MAY BE AT INCREASED RISK.

=====  
===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN. IF IRRITATION OR REDNESS PERSIST CONSULT A PHYSICIAN. SKIN-REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. INGESTION:DO NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. INHALATION OF OIL MIST OR FUMES, REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. GET MEDICAL HELP.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:475F,246C  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.  
Fire Fighting Procedures:DO NOT USE WATER STREAM DIRECTLY. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.  
Unusual Fire/Explosion Hazard:DO NOT HANDLE OR STORE NEAR HEAT OR FLAMES. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. DIKE AND KEEP PRODUCT OUT OF SEWERS & WATER COURSES. PUT WASTE IN A CONTAINER FOR PROPER DISPOSAL.  
Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:MINIMIZE SKIN CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE NEAR EXTREME HEAT OR OPEN FLAMES.  
Other Precautions:DO NOT CREATE MIST. DO NOT INHALE MIST OR VAPORS PRODUCED AT HIGH TEMPERATURES. IF WORKING WITH MIST OR FUMES, NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPORS FILTER MUST BE WORN. WASH THOROUGHLY AFTER HANDLING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. IF WORKING WITH MIST OR FUMES, USE NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VA

POR FILTER.

Ventilation:NORMAL OR MECHANICAL

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING.

Work Hygienic Practices:WASH HANDS AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORKING AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>540F,>282C

Melt/Freeze Pt:M.P/F.P Text:-75F,-59C

Vapor Pres: