View NSN Online: https://aerobasegroup.kr/nsn/9150-01-345-6134

## SOUTHWESTERN PETROLEUM CORP -- 704 HYDRAULIC OIL -- 9150-01-345-6134

Product ID:704 HYDRAULIC OIL

MSDS Date:04/22/1994

FSC:9150

NIIN:01-345-6134

MSDS Number: BLMXY === Responsible Party ===

Company Name: SOUTHWESTERN PETROLEUM CORP

Address:534 N MAIN ST

Box:789

City:FORT WORTH

State:TX ZIP:76101 Country:US

Info Phone Num:817-332-2336 Emergency Phone Num:817-332-23 36, CHEMTREC 800-424-9300

CAGE:14392

=== Contractor Identification ===

Company Name: SOUTHWESTERN PETROLEUM CORP

Address:534 N MAIN ST

Box:961005

City:FORT WORTH

State:TX ZIP:76106 Country:US

Phone:817-348-7235

CAGE:14392

======= Composition/Information on Ingredients ========

Ingred Name: RESIDUAL OILS, HYDROTREATED

CAS:64742-57-0

Fraction by Wt: SEE # 7%

Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: SOLVENT, DEWAXED RESIDUAL O

IL (PETROLEUM) CAS:64742-62-7

Fraction by Wt: SEE # 7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500 Fraction by Wt: SEE # 7%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY

PARAFFINIC CAS:64742-65-0

RTECS #:PY8038500 Fraction by Wt: SEE # 7%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: SOLVENT REFINED, HYDROTREATED LIGHT PARAFFINIC DISTILLATE

CAS:64742-55-8 RTECS #:PY8036500 Fraction by Wt: SEE # 7%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC

CAS:64742-56-9 RTECS #:PY8039500 Fraction by Wt: SEE # 7%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:REF

INED HEAVY PARAFFINIC DISTILLATES CAS:64741-88-4
Fraction by Wt: >97%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)
======================================
LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY BE MILDLY IRRITATING TO THE EYES.
PROLONGED OR REPEATED CONTACT MAY CAU
SE MILD IRRITATION AND
INFLAMMATION. ASPIRATION HAZARD.
Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, SKIN
INFLAMMATION, CHEMICAL PNEUMONIA.
Medical Cond Aggravated by Exposure:PERSONNEL WITH PRE-EXISTING SKIN
DISORDERS SHOULD AVOID CONTACT WITH THIS PRODUCT.
======================================
First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS
OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING.
WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL
ATTENTION. IN HALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL
ATTENTION.
======================================
======================================
Flash Point Method:COC
Flash Point:>354F,>179C
Autoign ition Temp:Autoignition Temp Text:>500F
Lower Limits: 0.9 %
Upper Limits:7 %
Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:WATER MAY CAUSE FROTHING. TOXIC GASES ARE
RELEASED DURING COMBUSTION.
======== Accidental Release Measures ======

=======

Spill Release Procedures:USE INERT ABSORBENT MATERIAL TO CONFINE SPILLS AND TO ABSORB MATERIAL. SCOOP INTO A DISPOSABLE CONTAINER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

========== Handling and Storage ============

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

Other Precautions: AVOID SKIN CONTACT. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

==

====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE LEVELS.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: PROTECTIVE CLO

THING AS REQUIRED TO AVOID

SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

========= Physical/Chemical Properties ===========

HCC:V6

Boiling Pt:B.P. Text:>559F,>293C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:> 5 Spec Gravity:0.9

Viscos

ity:SAE 15
Evaporation Rate & DIVEN
Solubility in Water:INSOLUBLE
Appearance and Odor:RED COLORED LIQUID,, LUBE OIL ODOR

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, OPEN FLAME
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
UNIDENTIFIED ORGANIC COMPOUNDS.

======= Disposal Considerations ===========

## Waste

Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liab

ility for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.