View NSN Online: https://aerobasegroup.com/nsn/8030-00-709-3327

## 

Product ID:WC-2240 MSDS Date:03/26/1990

FSC:8030

NIIN:00-709-3327

MSDS Number: BLNFQ === Responsible Party ===

Company Name: H. B. FULLER AUTOMOTIVE PRODUCTS, INC

Address:13650 EAST TEN MILE ROAD

Box:306

City:WARREN

State:MI ZIP:48090 Country:US

Info Phone Num:313-776-5000 Emergency Phone Num:31

3-776-5000

Preparer's Name: MIKE PELLNY

CAGE:FULLE

=== Contractor Identification ===

Company Name: H. B. FULLER AUTOMOTIVE PRODUCTS, INC

Address:13650 EAST TEN MILE ROAD

Box:306

City:WARREN

State:MI ZIP:48090 Country:US

Phone:313-776-5000

CAGE:FULLE

======= Composition/Information on Ingredients ========

Ingred Name: VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000 Fraction by Wt: 45-55%

Other REC Limits:NONE SPECIFIED OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192

Ingred

Name: PARAFFIN WAX CAS:8002-74-2 RTECS #:RV0350000 Fraction by Wt: 25-35% Other REC Limits: NONE SPECIFIED OSHA PEL:2 MG/M3 (FUME) ACGIH TLV:2 MG/M3 (FUME); 9192 Ingred Name: CARBON BLACK CAS:7440-44-0 RTECS #:FF5250000 Fraction by Wt: 2-5% Other REC Limits: NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:2 MG/M3 TDUST: 9293 Ingred Name: HYDRO-TREATED ALIPHATIC OIL CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 2-5% Other REC Limits: NONE SPECIFIED Ingred Name: CALCIUM SULFONATE BASED CORROSION I **NHIBITOR** CAS:61789-86-4 Fraction by Wt: 10-20% Other REC Limits: NONE SPECIFIED ============= Hazards Identification ======================== Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic: MAY CAUSE HEADACHES OR NAUSEA. MAY CAUSE EYE IRRITATION IF SPLASHED INTO THE EYE. MAY CAUSE DEFATTING OF SKIN. First Aid:INHALE: REMOVE PERSON TO FRESH AIR. SKIN: CLEAN AFFECTED AREA. EYES: CLEAN AFFECTED AREA WITH EYEWASH AND CONSULT PHYSICIAN. INGEST: CONSULT PHYSICIAN. TO BE TREATED AS SOLVENT INGESTION. Flash Point Method:TCC Flash Point:105F,41C Lower Limits:0.7 Upper Limits:6.0 Extinguishing Media: CO2, DRY CHEMICAL, FOAM Fire Fighting Procedures: VAPORS HEAVIER THAN AIR, WATER MAY CAUSE FROTHING.

Unusual Fire/Explosion Hazard: VAPORS HEAVIER THAN AIR. WATER MAY CAUSE

=====

FROTHING.

======= Accidental Release Measures =============
Spill Release Procedures:USE ABSORBENT, DIKE LARGE SPILLS, AVOID USE OF SPARKS OR OPEN FLAMES, VENTILATE WELL, AND USE NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:AVOID OPEN SPARKS OR FLAMES. Other Precautions:STORE ABOVE 40F.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF MAX OF 500 PPM IS EXCEEDED, USE CHARCOAL
TYPE. Ventilation:NONE REQUIRED Eye Protection:SAFETY GLASSES Other Protective Equipment:USE PROTECTIVE CLOTHING FOR CLEANLINESS AS DESIRED. Supplemental Safety and Health
======================================
HCC:F4 Boiling Pt:B.P. Text:313F,156C Vapor Pres:2.6 Vapor Density:+1 Spec Gravity:0.815 Evaporation Rate & Door: Reference:0.12 (TOLUENE) Appearance and Odor: BLACK PASTE, MILD SOLVENT ODOR Percent Volatiles by Volume:59
======================================
Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZERS. Stability Condition to Avoid:AVOID OPEN FLAMES. Hazardous Decomposition Products:CO, CO2, H2O Conditions to Avoid Polymerization:OPEN FLAMES AND/OR SPARKS
======== Disposal Considerations ============
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LOCAL ORDINANCES.
Disclaimer (provided with this information by the compiling agen

Disclaimer (provided with this information by the compiling agen

## cies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.