

SOUTHWEST PETRO-CHEM DIV WITCO CHEMICAL CORP -- 101 MOLY GREASE-HEAVY --  
9150-01-345-6148

===== Product Identification =====

Product ID:101 MOLY GREASE-HEAVY

MSDS Date:03/13/1991

FSC:9150

NIIN:01-345-6148

MSDS Number: BLNPC

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM DIV WITCO CHEMICAL CORP

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Info Phone Num:91

3-782-5800

Emergency Phone Num:913-782-5800

CAGE:70878

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM LUBRICATING OIL BASE STOCK (CAS NO  
64742-54-7,64742-65-0,64742-57-0)

Fraction by Wt: >85%

Other REC Limits:NONE SPECIFIED

OSHA PE

L:5 MG/M3 AS OIL MIST  
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 354F,>179C

Autoignition Temp:Autoignition Temp Text:>500F

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM  
EXPOSURES.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA.  
COOL

FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE & CONTAIN SPILL WITH INERT MATERIAL  
(SAND,EARTH,FULLERS EARTH ETC.).TRANSFER LIQUID TO DRUMS OR OTHER  
CONTAINERS FOR RECOVERY OR DISPOSAL.AREA MAY BE SLIPPERY.CARE  
SHOULD BE TAKEN TO AVOID FALLS. PREVENT MATERIAL FROM GETTING INTO  
SEWERS & WATERS

Neutralizing Agent:NO

T APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-THESE LUBRICANTS BECOME VERY  
VISCOUS WHEN STORED AT LOW TEMPERATURE.

Other Precautions:USE PRODUCT WITH CAUTION AROUND OPEN FLAMES, HEAT,  
SPARKS, PILOT LIGHTS & STATIC ELECTRICITY. AVOID PROLONGED OR  
REPEATED SKIN CONTACT. AVOID BREATHING VAPORS OR MISTS. WASH  
THOROUGHLY AFTER HANDLING OR BEFORE EATING OR DRINKING.

===== Exposure Controls/Personal

Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS IF TLV  
EXCEED.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

Protective Gloves:IMPERVIOUS

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE  
RE-USE. DISCARD OIL-SOAKED SHOES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

V

apor Density:>5  
Spec Gravity:0.9  
Solubility in Water:NO  
Appearance and Odor:GREY COLOR OIL, LUBE OIL ODOR  
Percent Volatiles by Volume:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES  
OF IGNITION  
Hazardous Decomposition Products:NO APPLICABLE INFORMATION FOUND.

===== Disposal Considerations =====

Wa  
ste Disposal Methods:DISPOSE OF CONTAMINATED DIKING MATERIAL  
ACCORDING TO CURRENT FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek c  
ompetent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.