

ASPEN PAINT -- STAIN, OIL TYPE, WOOD INTERIOR, WALNUT -- 8010-00-597-8225

=====  
Product Identification  
=====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR, WALNUT

MSDS Date:10/01/1991

FSC:8010

NIIN:00-597-8225

MSDS Number: BLTZQ

=== Responsible Party ===

Company Name:ASPEN PAINT

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603 (M-F 8:30 - 5:00)

E

mergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:D KIER

CAGE:DO051

=== Contractor Identification ===

Company Name:ASPEN PAINT

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Phone:(303) 573-1014

CAGE:DO051

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SK SOLVENT, MI

NERAL SPIRITS MIXTURE (SOLVENT 390)

CAS:8052-41-3

RTECS #:WT8925000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:SK SOLVENT:RAT/ORAL=>8 ML/KG. DERMAL=74\*

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NASAL/RESPIRATORY IRRIT,

ASPHIXIATION. SKIN: PROL

ONGED/REPEATED--DEFATTING & DRYING, IRRIT,

DERMATITIS. EYE: SEVERE IRRIT. INGESTION: IRRITATION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEM PNEUMONITIS (CAN BE FATAL).

PERMANENT BRAIN & NERVOUS SYS DAMAGE. CONCENTRATING AND INHALING PROD CAN BE FATAL.

Explanation of Carcinogenicity:NONE OF THE MATERIALS IN THIS PRODUCT IS ON THE IARC, NTP OR OSHA CARCINOGEN LIST.

Effects of Overexposure:INHAL: DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS AND ASPH

IXIATION. EYE: REDNESS, TEARING &

BLURRED VISION. INGEST: NAUSEA, VOMITING & DIARRHEA.

\*ML/KG

INHALATION +71400 PPM 4 HRS. BENZENE: RAT/ORAL=>5600 ML/KG.

INHALATION=13700 PPM

=====  
===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM EXPOSURE--RESTORE BREATHING, IF NEEDED.

EYE: FLUSH W/WATER--15 MIN, HOLDING EYELIDS OPEN. SKIN: WASH CONTAM

SKIN W/MILD SOAP & WATER. INGEST: DON'T INDUCE VOMITING. OBTAIN MEDICAL A TTEN

TION IMMEDIATELY. NOTE TO PHYSISIAN: MAIN HAZARD

FOLLOWING ACCIDENTAL INGESTION IS ASPIRATION OF LIQ INTO LUNGS

(CHEM PNEUMONITIS). CARDIAC ARRYTGMIAS HAVE BEEN REPORTED W/SOLVENT EXPOSURE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:112F,44C

Lower Limits:0.8

Upper Limits:5.0

Extinguishing Media:DRY CHEMICAL, CO2, FOAM, AND WATER FOG.

Fire Fighting Procedures:IN CONFINED FIRE SPACE USE ADEQUATE PROTECT CLOTHING & APPR

OVED POSITIVE PRESS SCBA. EXCLUDE AIR. DON'T USE  
WATER EXCEPT AS FOG TO COOL FIRE EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL  
IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN  
UPPER AND LOWER FLAMMABLE LIMITS.

===== Accidental Release Measures =====

Spill Release Procedures:NO IGNIT SOURCES. VENT AREA. ABSORB SPILL  
W/ABSORBENT (SAWDUST/SAND/VERMICULITE), PLACE IN CLOSED CNTNR. LRG

SPILL, DIKE AREA TO PREVENT MAT'L ENTERING WATER SYSTEMS/SEWERS.  
WEAR PROTECT EQUIP. NOTIFY APPROP ENVIRNMT AGENCY IF SPILL EXCEEDS  
220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENT AREA  
AWAY FROM HEAT/IGNITION SOURCES. AVOID CONTACT W/SKIN. AVOID BREATH  
VAPOR/MIST. KEEP AWAY FROM CHILDREN.

Other Precautions:GROUND CONTAINERS WHEN POURING & LIMIT FREE FALL TO  
MINIMIZE STATIC ELECTRICIT  
Y. EMPTY CONTAINERS MAY BE HAZARDOUS FROM  
RESIDUES OF PRODUCT/VAPOR. ALL CAUTIONS ON THIS MSDS APPLY TO THEM.  
CLOSE CONTAINER AFTER USE. DON'T INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER RESPIRATOR MUST BE WORN TO PREVENT  
THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV PEL IS  
EXCEEDED.

Ventilation:GENERAL VENT REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE  
NEEDED TO KEEP EXPOSURE LEVEL BELOW LIMITS LISTE  
D IN INGREDIENTS.

Protective Gloves:CHEM RESISTANT NITRILE/NEOPRENE/RUBBER

Eye Protection:FACE SHIELD OR CHEMICAL GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE.  
USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

TOXICITY TESTS CARRIED OUT FOR CARCINOGENICITY, TERATOGENICITY AND  
MUTAGENICITY HAVE BEEN NEGATIVE. DATA IS

INSUFFICIENT TO FURTHER  
CLASSIFY ACCORDING TO WHMIS CRITERIA.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:301 TO 402F  
Vapor Pres:>7.0 @ 38C  
Vapor Density:4.8  
Spec Gravity:0.87 (WATER=1)  
Viscosity:10"-- 25"#4FC  
Evaporation Rate & Reference:SLOWER N-BUTYL ACETATE  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:THIN LIQUID, MILD ODOR.  
Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

=

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.  
Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL  
IGNITION SOURCES.  
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE  
PRODUCED ON COMBUSTION.  
Conditions to Avoid Polymerization:AVOID EXCESSIVE HEAT, OPEN FLAME AND  
ALL IGNITION SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods:REC  
LAIM MAT'L OR TREAT AS HAZARD WASTE  
(#D001)(MAT'L & CNTNR). DISPOSE AT A LICENSED WASTE DISPOSAL CO OR  
INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. ALL DISPOSAL  
PROCEDURES MUST COMPLY W/FEDERAL, STATE & LOCAL REGULATIONS. REFER  
TO HZDCAUTION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants

ants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.