

GOULD INC RECORDING SYSTEMS DIV -- 23-5101-1 ELECTROSTATIC RECORDER TONER --
6850-01-008-3781

===== Product Identification =====

Product ID:23-5101-1 ELECTROSTATIC RECORDER TONER

MSDS Date:08/01/1990

FSC:6850

NIIN:01-008-3781

MSDS Number: BLVBR

=== Responsible Party ===

Company Name:GOULD INC RECORDING SYSTEMS DIV

Address:3631 PERKINS AVE

City:CLEVELAND

State:OH

ZIP:44114-4632

Country:US

Info Phon

e Num:716-853-7500

Emergency Phone Num:716-853-7500

CAGE:MO498

=== Contractor Identification ===

Company Name:GOULD INC RECORDING SYSTEMS DIV

Address:3631 PERKINS AVE

Box:City:CLEVELAND

State:OH

ZIP:44114-4632

Country:US

Phone:716-853-7500

CAGE:MO498

Company Name:GOULD INC., TEST AND MEASUREMENT GROUP

Address:8333 ROCKSIDE ROAD

Box:City:VALLEY VIEW

State:OH

ZIP:44125-6104

Country:US

Phone:216-328-7000

CAGE:96795

===== Composition/Information on Ingredients =====

Ingred Name:C

ARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 0.4%
Other REC Limits:3.5 MG/M3
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:ISODODECANE (C10, C11 ISOPARAFFINIC HYDROCARBON)
CAS:31807-55-3
Fraction by Wt: 2-3%
Other REC Limits:200 PPM

Ingred Name:HYDROTREATED HEAVY NAPHTHA
CAS:64742-48-9
Fraction by Wt: 96.5-97%
Other REC Limits:300 PPM

Ingred Name:HEAVY AROMATIC NAPHTHA
CAS:64742-94-5
Fraction by Wt: 0.6-1.0%
Other REC Limits:100 PPM

=====
Hazards Id
entification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION: MAY CAUSE MUCOUS
MEMBRANE IRRITATION, AND CNS EFFECTS. EYE:IRRITATION.
SKIN:DEFATTING OF THE SKIN AND IRRITATION. INGESTION: MAY CAUSE
DIARRHEA, CNS DEPRESSION. SMALL AMOUNTS ASPIRA TED INTO LUNGS MAY
RESULT IN SEVERE PULMONARY INJURY OR DEATH. CHRONIC:DERMATITIS,
CHEMICAL PNEUMON
ITIS, KIDNEY DAMAGE.
Explanation of Carcinogenicity:THIS PRODUCT HAS NOT SHOWN ANY EVIDENCE
OF BEING CARCINOGENIC.
Effects of Overexposure:OVEREXPOSURE MAY LEAD TO RESPIRATORY
IRRITATION, NAUSEA, FATIGUE, DIZZINESS, HEADACHES, CENTRAL NERVOUS
SYSTEM EFFECTS, RESPIRATORY ARREST, OR UNCONSCIOUSNESS, DERMATITIS
AND EYE IRRITATION.
Medical Cond Aggravated by Exposure:SKIN, KIDNEY AND RESPIRATORY
DISEASES.

=====
First Aid Measures =====

Firs

t Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE :IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION:GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

=====
===== Fire Fighting Measures =====

FI
ash Point Method:TCC
Flash Point:100F,38C
Lower Limits:0.8%
Upper Limits:7%
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:EVACUATE AREA. WEAR PROTECTIVE EQUIPMENT AND SCBA. SHUT OFF SOURCE, IF POSSIBLE CONTAIN SPILL. PROTECT FROM IGNITION. KEEP OUT OF WATER SOURCES AND SEWERS. ABSORB IN A DRY, INERT MATERIAL. TRANSFER TO DISPOSAL DRUMS USING NON-SPARKING EQUIPMENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINERS CLOSED WHEN NOT IN USE. EMPTY CONTAINERS MAY BE HAZARDOUS.
Other Precautions:AVOID CONTACT WITH EYES, SKIN, OR CLOTHING. AVOID BREATHING VAPORS. WEAR PROTECTIVE EQUIPMENT AND/OR GARMENTS. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROVIDE MEANS OF CONTROLLING LEAKS AND SPILLS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORG

ANIC VAPOR CARTRIDGES ARE RECOMMENDED FOR
CONCENTRATIONS EXCEEDING THE RECOMMENDED EXPOSURE LEVEL.
Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN
ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.
Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL
Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD
Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.
Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NOT
EAT, DRINK OR SMOKE IN WORK
AREA.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:=148.9C, 300.F
B.P. Text:300F,149C
Vapor Pres:1
Spec Gravity:0.75-0.80
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID, MILD ISOPARAFFINIC HYROCARBON ODOR.
Percent Volatiles by Volume:>99

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER HYDROCARBON COMPOUNDS DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR
OR DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND
FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information)

by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.