

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- BEACON 325 -- 9150-00-911-7823
===== Product Identification =====

Product ID:BEACON 325

MSDS Date:07/01/1985

FSC:9150

NIIN:00-911-7823

MSDS Number: BLWGL

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-656-5949 FAX: 713-656-363

1

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

Company Name:TELEMECHANICS INC

Address:1636 FIFTH AVE

Box:City:BAY SHORE

State:NY

ZIP:117

06
Country:US
Phone:516-231-3833
CAGE:57712

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. INGESTION:
THIS PRODUCT HAS A LOW DEGREE OF TOXICITY, BUT MINUTE AMOUNTS
ASPIRAT
D INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE MILD
TO SEVERE PULMONARY INJURY. PR OLONGED OR REPEATED SKIN CONTACT
MAY CAUSE SKIN IRRITATION.
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT WITH THIS
PRODUCT TENDS TO REMOVE SKIN OILS POSSIBLY LEADING TO IRRITATION
AND DERMATITIS.
Medical Cond Aggravated by Exposure:NONE RECOGNIZED

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL
IRRITATION
SUBSIDES. SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN
THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE
AND CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL A
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:415F,213C
Autoignition Temp:Autoignition Temp Text:>260C
Lower Limits:1.0
Upper Limits:12.0
Extinguishing Media:FOAM, WATER SPRAY (FOG), DRY CHEMICAL, CARBON

DIOXIDE AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.

Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS. USE SUPPLIED-AIR BREATHING EQUIPMENT

Unusual Fire/Explosion Hazard:THIS MATERIAL WILL EMIT TOXIC DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR

OTHER SUITABLE ABSORBENT TO SPILL AREA. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA.

Other Precautions:NONE 30JAN92CD
68500130464160BYN5A

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:500F,260C
Vapor Pres:5
Spec Gravity:0.94
Viscosity:280 ASTM D217
Evaporation Rate & Reference: