

P-T TECHNOLOGIES INC -- PF DEGREASER SOLVENT -- 7930-01-328-5960

=====
Product Identification
=====

Product ID:PF DEGREASER SOLVENT

MSDS Date:12/13/1995

FSC:7930

NIIN:01-328-5960

MSDS Number: BLXLQ

=== Responsible Party ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Info Phone Num:800-441-7874

Emergency Phone Num:800-441-7874

C

AGE:0JVH6

=== Contractor Identification ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

Box:City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Phone:813-726-4644

CAGE:0JVH6

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON, TRADE SECRET REG #:80100071-5000P,
MONOCYCLIC TERPENE

CAS:68647-72-3

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 RA

T,ORAL: >5G/KG OF BODY WT.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:MAY CAUSE

IRRIT,TEARING,REDNESS.DONT INJURE EYE.SKIN:PROL/REP CONTACT MAY CAUSE DEFATTING,DRYNESS.CONT DRYNESS MAY CAUSE DERM.INHAL:EXCESS VAP INHAL CAN CAUSE IRRIT OF RESP TRACT,NAUSEA,DIZZ,HEAD .INGEST:HAS LOW ORDER OF ACUTE ORAL TOXICITY BUT INGEST LG QUANT MAY CAUSE NAU,VOMIT,GI IRRIT.MAY CAUSE INJURY

(SUPPLEM)

Effects of Overexposure:EYE IRRIT,TEARING,REDNESS. DEFATTING,DRYNESS OF SKIN, DERMATITIS. IRRIT OF RESP TRACT,NAU,DIZZ,HEADACHE.NAU,VOMITING,GI IRRIT, INJURYT IF ASPIRATED INTO LUNGS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/WTER FOR 15MINS.IRRIT PERSISTS CONTACT PHYSICIAN.SKIN:WASH THOROUGHLY W/SOAP/WATER.REMOVE CONTAMIN CLOTH.INHAL:IF AFFECTED BY VAP GET FRESH AIR.BREATH DIFFICULT SEE PHYSICIAN.INGEST:DONT I NDUCE VOMIT.PRODUCT CONTAINS HYDROCARBON.SEE PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:144F,62C

Autoignition Temp:Autoignition Temp Text:410F

Lower Limits:1.3

Upper Limits:8.9

Extinguishing Media:EXTINGUISH W/CO2, FOAM, OR DRY CHEMICAL. CLASS B FIRE PROCEDURES.

Fire Fighting Procedures:EXTINGUISH W/CO2, FOAM, OR DRY CHEMICAL. CLASS B FIRE PROC EDURES.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.CAN FORM COMBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:LAND:REMOVE IGN SOURCES.CONTAIN SPILL.RECOVER FREE PRODUCT.ABSORB W/SUITABLE CHEMC ABSORBENT FOR DISPO VIA INCINERATION OR BURIAL IN APPROVED LANDFILL.OBSERVE LOC/STATE/FED REGULATIONS.WATER:REMOVE BY SKIM/USE OF SUITABLE ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFA

CTURER.

===== Handling and Storage =====

Handling and Storage Precautions:ELECTROSTATIC ACCUMULATION

HAZ:UNKN,USE PROPER GROUNDING PROCEDURES.STORAGE TEMP:AMBIENT.KEEP AWAY FROM HEAT SOURCES,OPN FLAMES,OTHER IGN SOURCES.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.PHOTOCHEM REACTIVE MATL PRESENT-YES,