

DAP INC -- ACRYLIC LATEX CAULK -- 8030-01-261-6865

=====
Product Identification
=====

Product ID:ACRYLIC LATEX CAULK
MSDS Date:03/28/1989
FSC:8030
NIIN:01-261-6865
MSDS Number: BMBYJ
=== Responsible Party ===
Company Name:DAP INC
Address:5300 HUBERVILLE RD
Box:277
City:DAYTON
State:OH
ZIP:45401-0277
Country:US
Info Phone Num:800-543-3840
Emergency Phone Num:800-543-3840
CAGE:90300
=== Contractor
Identification ===
Company Name:DAP INC.
Box:277
City:DAYTON
State:OH
ZIP:45401-0277
Country:US
Phone:513-253-7154/800-543-3840
CAGE:90300

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS (ALL INGREDIENTS ARE NOT
REGULATED BY OSHA AND ARE CONSIDERED TRADE SECRETS).
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 4 G/L LESS WATER AND EXEMPT SOLVENTS. 3 G/L -
MATERIAL.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

=====

=====
Fire Fighting Measures
=====

Flash Point:NONE

Upper Limits:AMBER FL

Fire Fighting Procedures:N/K WATER FOG, CHEMICAL FOAM, DRY CHEMICAL,
CO2. WEAR NIOSH/MSHA APPRVD

Unusual Fire/Explosion Hazard:SCBA/FULL PROT EQUIP WHEN FIRE FIGHTING
IN CONFINED SPACES. MATL WILL NOT BURN UNLESS PREHEATED. COOL
FIRE-EXPOSED CNTNRS W/WATER.NONE

=====
Exposure Controls/Personal Protection
=====

Supplemental Safety and Health

=====
Phy
sical/Chemical Properties
=====

HCC:N1

Solubility in Water:N/

Appearance and Odor:K WIDE RANGE 0.860 SEE SUPDAT0F(POUR PT)SEE SUPD

=====
Stability and Reactivity Data
=====

YESHEAT AND OPEN FLAMES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information
to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.