

CAAP CO INC -- CAAPCOAT C-W4 WHITE POLYURETHANE RAIN EROSI -- 8010-01-132-2976

=====
Product Identification
=====

Product ID:CAAPCOAT C-W4 WHITE POLYURETHANE RAIN EROSI

MSDS Date:11/01/1991

FSC:8010

NIIN:01-132-2976

Kit Part:Y

MSDS Number: BMCFQ

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Preparer's Name:CHRISTINE L SLEDGE

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 46.5%

Other REC Limits:150 PPM STEL

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000

LBS

Ingred Name:METHYLISOBUTYLKETONE (SARA 313)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 16.6%

Other REC Limits:75 PPM STEL

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 1.9%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:RESIDUAL METHYLENE BIS(4-CYCLOHEXYLISOCYANATE)

CAS:5124-30-1

RTECS #:NQ9250000

Fraction

by Wt: 0 - 0.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:.01 PPM CEILING

ACGIH TLV:0.005 PPM TWA

Ingred Name:ISOCYANATE TERMINATED POLYESTER PREPOLYMER

CAS:54954-83-5

Fraction by Wt: 35.0%

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 546 G/L, 4.55 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 607 G/L, 5.06 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalatio

n:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES, IRRITATE SKIN & CAUSE RESPIRATORY IRRITATION UPON INHALATION. CHRONIC: REPEATED/PROLONGED EXPOSURE MAY CAUSE DEFATTING OF SKIN, DERMATITIS & POSSIBLE SENSITIZATION. INHALATION OF VERY HIGH VAPOR CONCENTRATIONS OR PROLONGED EXPOSURE MAY CAUSE NEURAL DYSFUNCTION, KIDNEY AND LIVER DAMAGE.

Effects of Overexposure:VAPOR EXPOSURE: BURNING EYES, HEADACHE,

DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, NAUSEA. CONTACT: MAY CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR EYES.

Medical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE, SKIN AND RESPIRATORY DISORDERS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER, GET IMMEDIATE MED ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN W/SOAP & WATER. REPEAT IF NECESSARY. IF SIGNS & SYMPTOMS OF EXPOSURE EXIST, GET IMMEDIATE MED

ATTENTION. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY, GET IMMEDIATE MED ATTENTION. INGESTION: DON'T INDUCE VOMITING, GET IMMEDIATE MED AID. IF VOMITING OCCURS KEEP VICTIM'S HEAD BELOW HIPS (PREVENT ASPIRATION OF MATERIAL).

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:68.0F,20.0C

Lower Limits:1.0

Upper Limits:8.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL. *(COATING SOLUTION).

Fire Fighting Procedures:

USUAL FOR FLAMMABLE LIQUIDS. PRODUCT ISN'T MISCIBLE W/WATER. WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIREFIGHTERS WEAR SCBA & PROTECT CLOTHING.

Unusual Fire/Explosion Hazard:NONE, PRODUCT IS A FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES & DO NOT SMOKE IN AREA. WEAR PROTECTIVE EQUIP (SOLVENT RESISTANT GLOVES, APRON, BOOTS & PRESSURE DEMAND SCBA/POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR) CONTAIN SPILL

W/ABSORB DIKES. SOAK UP W/ABSORB. CLEAN UP & CONTAIN SECURELY.
SWEEP & WET MOP**

Neutralizing Agent:N/K **W/SOAP & WATER. VENTILATE AREA AS WELL AS
POSSIBLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT WEAR CONTACT LENSES WHEN USING
THIS PRODUCT AS CONTACT LENSES CONTRIBUTE TO THE SEVERITY OF AN EYE
INJURY.

Other Precautions:FOR MORE COMPLETE HEALTH AND SAFETY INFOMATION ON USE
OF COATINGS CONTAINING RESIDU
AL ISOCYANATE PLEASE CONSULT MOBAY'S
HEALTH AND SAFETY INFORMATION BROCHURE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WITH VAPORS/MISTS WEAR APPROPRIATE NIOSH
APPROVED RESPIRATOR. APPROPRIATE RESPIRATORS INCLUDE A FULL
FACEPIECE OR PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC
VAPORS/MISTS, PRESS DEMAND SCBA, O R POS PRESS AIR-SUPPLIED
RESPIRATOR.

Ventilation:SPRAY BOOTH REQUIRED--SPRAY APPLICATIONS. ONLY
TRAINED/P
ROTECTED PEOPLE IN AREA. EXHAUST VENT SHOULD BE
SUFFICIENT***

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:SOLVENT RESISTANT SAFETY GOGGLES

Other Protective Equipment:FULL PERMEATION RESISTANT PROTECTIVE SUIT
(HEAD COVERING, FACE SHIELD, GLOVES, OVERSHOES) DURING MIXING,
SPRAYING.

Work Hygienic Practices:EYEWASH AND SAFETY SHOWERS SHOULD BE NEARBY &
READY FOR USE. WASH WELL WITH SOAP AND WATER AFTER HANDLING
PRODUCT.

Supplemental Safety and Health

KEY1:F3. TO KEE

P THE AIRBORNE CONCENTRATIONS BELOW PEL'S. VENTILATION
SYSTEMS SHOULD BE DESIGNED TO DRAW AIR PAST THE OPERATOR, THEN PAST
THE SOURCE OF THE VAPOR, AND THEN TO THE EXHAUST, NOT THE REVE RSE.
VENTILATION SHOULD BE IN ACCORDANCE WITH ACGIH GUIDELINES AS
CONTAINED IN ITS "INDUSTRIAL VENTILATION" PUBLICATION.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:241 TO 281F

Decomp Temp:Decomp Text:675F,357C

Vapor Pres:.8

Vapor Density:3.6

Spec Gravity:1.007(WATER=1)*

pH:5.5 *

Viscosity:***

Evaporation Rate & Reference:0.85 (BU AC=1)

Solubility in Water:INSOLUBLE *

Appearance and Odor:WHITE AROMATIC LIQUID (COATING SOLUTION)

Percent Volatiles by Volume:63.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:PRODUCT SHOULD BE KEPT AWAY FROM ALL
IGNITION SOURCES, HOT SURFACES, AND T
EMPERATURES ABOVE 100 F.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF NITROGEN, AS WELL AS TRACES OF HCN MAY BE RELEASED DURING
COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN APPROP DESIGNED & LICENSED
INCINERATOR IS PREFERRED; RCRA HAZARDOUS IGNITABLE WASTE. DISPOSE
ACCORDING TO FED, STATE & LOCAL REGS. WHEN C-W4, CURING
AGENT/ACCELERATOR ARE MIXED & SOLVE NT EVAPORATED.
SOLID IS
NON-HAZARD LANDFILL ITEM.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this
information to their
particular situation.