

MOBIL OIL CORPORATION -- SHC 634 -- 9150-01-149-9166

===== Product Identification =====

Product ID:SHC 634

MSDS Date:09/19/1991

FSC:9150

NIIN:01-149-9166

MSDS Number: BMDVS

=== Responsible Party ===

Company Name:MOBIL OIL CORPORATION

Address:BEAUMOUNT REFINERY INTERSTATE 10

Box:3311

City:BEAUMONT

State:TX

ZIP:77704

Country:US

Info Phone Num:800-662-4525 OR 703-849-3265

Emergency Phone Num:212-883

-4411 OR 800-662-4525

CAGE:19135

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

Company Name:MOBIL OIL CORPORATION

Address:BEAUMOUNT REFINERY INTERSTATE 10

Box:3311

City:BEAUMONT

State:TX

ZIP:77704

Country:US

Phone:609-737-4411/800-424-9300(CHEMTREC)

CAGE:19135

===== Composition/Information on Ingredients =====

Ingred Name:

ALKENES C>10 ALPHA POLYMO (TOTAL PERCENTAGE (WT) OF
INGREDIENTS 1 & 2 IS >95).

CAS:68527-08-2

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 AS OIL MISTS

ACGIH TLV:5 MG/M3 AS OIL MISTS

Ingred Name:HEXANEDIOIC ACID, DITRIDECYL ESTER

Other REC Limits:NONE SPECIFIED

Ingred Name:DIPHENYLAMINE/BENZENAMINE, N-PHENYL

CAS:122-39-4

RTECS #:JJ7800000

Fraction by Wt: 0.05%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9192

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS - NONTOXIC

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYE/SKIN:MAY CAUSE

IRRITATION.INHALATION:MAY CAUSE RESPIRATORY

IRRITATION,DIZZINESS,NAUSEA,UNCONSCIOUSNESS.INGESTION:NOT EXPECTED

TO BE A PROBLEM.CHRONIC-NONE KNOWN.

Effects of Overexposure:MAY CAUSE EYE OR SKIN IRRITATION. INHALATION

MAY CAUSE RESPIRATORY IRRITATION,

DIZZINESS, NAUSEA,

UNCONSCIOUSNESS. NOT EXPECTED TO BE A PROBLEM BY INGESTION.

Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST.INHALATION:REMOVE TO

FRESH AIR.PROVIDE CPR IF NEEDED.EYES:FLUSH WITH WATER FOR 15

MINUTES,HOLDING EYELIDS OPEN.SKIN:WASH WITH SOAP &

WATER.INGESTION:NOT EXPECTED T O BE A PROBLEM.IF UNCOMFORTABLE,SEEK

MEDICAL ADVICE.

=====

==== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>480F,>249C

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measur
es =====

Spill Release Procedures:REMOVE SOURCES OF HEAT/IGNITION,PROVIDE
ADEQUATE VENTILATION,CONTAIN LEAK.ABSORB ON FIRE RETARDANT TREATED
SAWDUST,DIATOMACEOUS EARTH,ETC. SHOVEL UP AND TRANSFER TO A
CONTAINER FOR DISPOSAL. REPORT SPILLS AS REQUIRED TO AUTHORITIES
(800-424-8802).

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL PLACE.KEEP AWAY
FROM HEAT,FLAME & STRONG OXIDANTS.

Other

Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH
VAPOR OR MIST CONCENTRATIONS EXPECTED, USE RESPIRATOR APPROVED FOR
ORGANIC VAPORS AND MISTS.

Ventilation:MECHANICAL VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION AND S
AFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE P/N A UNDER THE SAME
NSN.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: