

PETRO CANADA INC -- RALUBE 40, 40CP, 1340, 1740 -- 9150-01-279-6506

===== Product Identification =====

Product ID:RALUBE 40, 40CP, 1340, 1740

MSDS Date:02/15/1991

FSC:9150

NIIN:01-279-6506

MSDS Number: BMGZY

=== Responsible Party ===

Company Name:PETRO CANADA INC

Address:PETRO CANADA CENTER

Box:2844

City:CALGARY, ALBERTA

Info Phone Num:403-296-3000

Emergency Phone Num:403-296-3000

CAGE:MO401

===

Contractor Identification ===

Company Name:PETRO CANADA INC

Address:PETRO CANADA CENTER

Box:2844

City:CALGARY, ALBERTA

Phone:403-296-3000

CAGE:MO401

Company Name:PETRO-CANADA/CANADIAN COMMERCIAL CORP

Address:150 6TH AVE SW

Box:2844

City:CALGARY

State:AB

Country:CA

Phone:403-296-3000

CAGE:14051

===== Composition/Information on Ingredients =====

Ingred Name:SEVERELY HYDROTREATED HYDROCARBON OIL

Fraction by Wt: >85%

Other REC Limits:NONE SPECIFIED

Ingred Name:PERFORMANCE ADDITI

VES

Fraction by Wt: 5000 MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALE-IF SPRAYED OR MISTED MAY CAUSE CHEMICAL PNEUMONITIS. SKIN AND EYES-MILDLY IRRITATING TO EYES. PROLONGED OR REPEATED CONTACT WITH SKIN MAY CAUSE MILD IRRITATION AND POSSIBLE DERMATITIS. INGEST-L OW TOXICITY ON INGESTION.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATI

ONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:INGESTION-HAS LAXATIVE EFFECTS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: COPIOUS WARM WATER FLUSH - 15 MINUTES. PHYSICIAN ASSESSMENT IF EYES INFLAMED. SKIN: REMOVE CONTAMINATED CLOTHING - LAUNDRER BEFORE REUSE. SOAP & WATER WASH. INHALE: EVACUATE TO FRESH AIR. APPLY C PR IF REQU

URED. GIVE OXYGEN IF AVAILIABLE. INGEST: DO NOT INDUCE VOMITING. FORCE FLUIDS. ACTIVATED CHARCOAL TABLETS.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:421F,216C

Autoignition Temp:Autoignition Temp Text:>365C

Extinguishing Media:DRY CHEMICAL OR CARBON DIOXIDE FOR SMALL FIRES. WATER SPRAY OR FOAM FOR LARGE FIRES.

Fire Fighting Procedures:CONTAIN SPILL. COVER WITH EXTINGUISHING AGENT. COOL FIRE EXPOSED CONTAINERS WITH WATER SP

RAY. DO NOT POINT WATER STREAM INTO BURNING OIL. WEAR A SCBA.

Unusual Fire/Explosion Hazard:POSSIBLE RELEASE OF TOXIC CHLOROCARBONS & OXIDES OF SULFUR IF OIL IS BURNING. ADDITION OF WATER OR FOAM MAY CAUSE FROTHING. DO NOT CUT, DRILL OR WELD CONTAINERS

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. ABSORB WITH INERT ABSORBENT SUCH AS DRY CLAY, SAND OR DIATOMACEOUS EARTH, COMMERCIAL SORBENT, OR RECOVER USING PUMPS.

