

CON-LUX COATINGS INC -- TT-V-71H VARNISH INTERIOR, FLOOR & TRIM -- 8010-00-165-4420

=====
Product Identification
=====

Product ID:TT-V-71H VARNISH INTERIOR, FLOOR & TRIM

MSDS Date:10/20/1986

FSC:8010

NIIN:00-165-4420

MSDS Number: BMNPP

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908-287-4

000 / FAX 908-287-9288

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,
HYDROTREATED

CAS:64742-47-8

RTECS #:OA5504000

Fraction by Wt: 52.87%

=====
Hazards Identifica

tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:
RESPIRATORY TRACT IRRITATION, HEADACHE, NAUSEA, & DIZZINESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION: RESPIRATORY
TRACT IRRITATION, HEADACHE, NAUSEA, & DIZZINESS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR & RESTORE RESPIRATION. EYES:
FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.
INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DON'T INDUCE
VOMITING. IF SPONTANEOUS VOMITING OCCURS KEEP HEAD AT OR BELOW
KNEE LEVEL TO PREVENT ASPIRATION INTO LUNGS. OBTAIN MEDICAL
ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F
Extinguishing Media
:FOAM, CO2, DRY CHEMICAL, OR WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES W/EXTINGUISHING MEDIA. WATER
MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. WEAR PROTECTIVE
EQUIPMENT. CONTAIN SPILL W/ABSORBENT MATERIAL & PUT INTO VAPOR
TIGHT CONTAINERS. PREVENT MATERIAL FROM CONTACTING ANY WATER
SOUR
CES OR SEWERS LEADING TO SUR FACE WATERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREA DESIGNED TO COMPLY
W/ANSI/NFPA FLAMMABLE/COMBUSTIBLE LIQUIDS. GROUND CONTAINERS WHEN
POURING LIQUID/POWDERS TO AVOID STATIC CHARGE.
Other Precautions:READ & UNDERSTAND MANUFACTURERS SAFETY PRECAUTIONS
BEFORE HANDLING. PREVENT SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protect

ion:IN OUTDOOR OR OPEN AREAS, USE APPROVED
RESPIRATOR FOR SOLID AIRBORNE PARTICLES DURING SPRAY APPLICATION.
IN RESTRICTED VENTILATED AREA, USE APPROVED RESPIRATOR TO REMOVE
COMBINATION OF PARTICLES & VAP OR.
Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60.66%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stabilit
y Condition to Avoid:EXTREME HEAT, SPARKS, & OPEN FLAME
Hazardous Decomposition Products:HAZARDOUS FUMES WHEN HEATED

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly
or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.