

MOBIL OIL CORP -- DELVAC 1210 -- 9150-00-189-6727

===== Product Identification =====

Product ID:DELVAC 1210

MSDS Date:01/07/1992

FSC:9150

NIIN:00-189-6727

MSDS Number: BMPZD

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411/CHEMTREC 800-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (TOTAL % OF ING
1, 2 AND 3 IS >90)

CAS:64742-54-7

RTECS #:PY8035500

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL
CAS:64742-65-0
RTECS #:PY8038500
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC
CAS:64742-56-9
RTECS #:PY8039500
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:BUTENE HOMOPOLYMER
CAS:9003-29-6
Fraction by Wt: 405F,>207C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY CHEMICAL. DO NOT
USE A DIRECT
STREAM OF WATER. PRODUCT WILL FLOAT & CAN BE
REIGNITED.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL
FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:CARBON MONOXIDE AND CARBON DIOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF HEAT/IGNITION,PROVIDE
ADEQUATE VENTILATION,CONTAIN LEAK.ABSORB ON FIRE RETARDANT
TREATED
SAWDUST,DIATOMACEOUS EARTH,ETC. SHOVEL UP AND TRANSFER TO A
CONTAINER FOR DISPOSAL. REPORT SPILLS AS REQUIRED TO AUTHORITIES
(800-424-8802).

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL PLACE.KEEP AWAY
FROM HEAT,FLAME & STRONG OXIDANTS.
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH
THOROUGHLY AFTER HANDLING. DO NOT BREATHE MISTS OR VAPORS.

===== Exposure Co

ntrols/Personal Protection =====

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE RESPIRATOR APPROVED FOR ORGANIC VAPORS AND MISTS.

Ventilation:MECHANICAL VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HY
GIENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: