

OMEGA CHEMICAL CORP -- OMEGA 2775 -- 8030-00-213-3279

===== Product Identification =====

Product ID:OMEGA 2775

MSDS Date:02/01/1991

FSC:8030

NIIN:00-213-3279

MSDS Number: BMPZJ

=== Responsible Party ===

Company Name:OMEGA CHEMICAL CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Info Phone Num:312-586-8000

Emergency Phone Num:312-586-8000

CAGE:OB5U9

=== Contractor Ide

ntification ===

Company Name:OMEGA CHEMICAL CORD; SUCCESSOR TO MSCI

CAGE:OB5U9

Company Name:OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Phone:312-586-8000, 800-424-9300

CAGE:OB5U9

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED DISTILLATE, LIGHT

CAS:64742-47-8

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM

Ingred Name:PETROLEUM HYDROCARBON

CAS:64742-61-6

Other REC Limits:NO

NE SPECIFIED
ACGIH TLV:5 MG/M3

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYE & RESPIRATORY TRACT & MAY CAUSE HEADACHES, DIZZINESS OR NAUSEA. EXTREME CONCENTRATIONS IN CONFINED SPACES MAY CAUSE UNCONSCIOUSNESS. MAY CAUSE IRRITATION &/OR BURNS TO EYES. EXCESSIVE OR REPEATED CONTACT WITH SKIN MAY CAUSE IRRITATION.
Medical Cond Aggravated by Exposure:NONE CURRENTLY KNOWN.

=
=====
First Aid Measures
=====

First Aid:WASH AREAS OF CONTACT WITH GENEROUS AMOUNTS OF WARM WATER AND MILD SOAP. FOR EYES, FLUSH THOROUGHLY WITH WATER & SEEK MEDICAL ATTENTION IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:145F,63C

Extinguishing Media:CO2, FOAM.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:IF OUTDOOR, ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL IGNITION SOURCES AND REMOVE WITH ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:THIS CONTAINER MAY BE HAZARDOUS WHEN EMPTIED. EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUE (VAPOR OR LIQUID). OBSERVE ALL LABELED HAZARD PRECAUTIONS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:REQUIRED WHEN CONCENTRATIONS OF HAZARDOUS MATERIALS ARE AT/ABOVE THE TLV SET BY ACGIH OR OSHA.
Ventilation:SHOULD BE SUFFICIENT TO REDUCE THE LEVELS BELOW THE TLV OR PEL O

F THE PRODUCT OR ANY OF ITS CONSTITUENTS.

Protective Gloves:NEOPRENE GLOVES

Eye Protection:SAFETY GOGGLES, FACE SHIELD--OSHA *

Other Protective Equipment:*1910.133 A AND ANSI Z871.1968.

Work Hygienic Practices:REASONABLE CARE AND PRECAUTIONS WHEN HANDLING THIS MATERIAL ARE STRONGLY RECOMMENDED. LAUNDER CONTAM CLOTH BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:>300F,>149C

Spec Gravity:0.9 (W

ATER=1)

Evaporation Rate & Reference: