

ACCUMETRIC INC -- 200 FLUID,20 CS -- 9150-00-487-4219

===== Product Identification =====

Product ID:200 FLUID,20 CS

MSDS Date:10/15/1990

FSC:9150

NIIN:00-487-4219

MSDS Number: BMQDD

=== Responsible Party ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:502-769-3385 (72-1; DEBBY)

CAGE:58149

=

== Contractor Identification ==

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

===== Composition/Information on Ingredients =====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYE:MAY CAUSE MILD REDNESS & DRYNESS SIMILAR TO WINDBURN.SKIN:A SINGLE PROLONGED EXPOSURE CAUSES NO KNOWN ADVERSE EFFECT.INHALE:NO IRRITATION/INJURY FROM RELATIVELY SHORT EXPOSURE OF < 8 HOURS.O RAL:SMALL AMOUNTS SHOULD NOT INJURE.LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.CHRONIC-NO KNOWN ADVERSE EFFECT.

Effects of Overexposure:MAY CAUSE MILD EYE REDNESS & DRYNESS SIMILAR TO WINDBURN. A SINGLE PROLONGED SKIN EXPOSURE CAUSES NO KNO WN ADVERSE

EFFECT. NO IRRITATION/INJURY FROM RELATIVELY SHORT INHALATION EXPOSURE OF < 8 HOURS. INGESTION OF SMALL AMOUNTS SHOULD NOT INJURE. LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL, MAY AGGRAVATE PRE-EXISTING CONDITIONS SUCH AS ALLERGIES ON CERTAIN PEOPLE.

=====  
===== First Aid Measures =====

First Aid:SEEK MEDICAL HELP IF SYMPTOMS DEVELOP.INHALATION/ORAL:NO FI RST AIR SHOULD BE NEEDED.EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN.SKIN:WIPE OFF AND FLUSH WITH WATER.

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:400F,204C

Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY CHEMICAL. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT MAY FLOAT & CAN BE REIGNITED.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED B

REATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:SILICONE DIOXIDE, CARBON DIOXIDE AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION.STOP LEAK.DIKE THE SPILLS.USE PUMP TO TRANSFER LARGE SPILLS TO CONTAINER FOR DISPOSAL.REMAINING LIQUID/SMALL SPILLS CAN BE TAKEN UP ON SAND,CLAY,EARTH & SHOVEL

D INTO CONTAINERS.PREVENT RUN-OFF TO ENTER WATERWAYS.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN TIGHTLY CLOSED CONTAINERS AT AMBIENT TEMPERATURES (5-25C) AWAY FROM OXIDIZERS.

Other Precautions:"EMPTY" CONTAINERS MAY RETAIN RESIDUE AND CAN BE DANGEROUS.DO NOT PRESSURIZE,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND OR EXPOSE SUCH CONTAINERS TO HEAT,FLAME,SPARKS.THEY MAY EXPLODE AND

D

CAUSE INJURY/DEATH.AVOID REPEATED/PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF VAPORS OR MISTS PRESENT, WEAR NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE ADEQUATE VENTILATION. USE LOCAL EXHAUST FANS AS NECESSARY.

Protective Gloves:WASHING AT MEALTIME & END OF THE SHIFT

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK

CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES REQUIRE THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:< 5 @ 77F

Spec Gravity:0.95

Solubility in Water:< 0.1%

Appearance and Odor:COLORLESS LIQUID WITH VERY LITTLE ODOR

Percent Volatiles by Volume:< 5

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES

Hazardous Decomposition Products: SILICONE DIOXIDE, CARBON DIOXIDE AND  
TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL STATE AND  
FEDERAL REGULATIONS. PRODUCT IS AN OIL. SPILLS TO US SURFACE WATERS

OR WATERCOURSE OR SEWER THAT CAUSE A VISIBLE SHEEN MUST BE REPORTED  
TO THE NATIONAL RESPONSE CENTER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional  
advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.