

CHEMICAL PACKAGING CORP -- 2-955 DRY MOLY -- 9150-00-827-5488

=====
Product Identification
=====

Product ID:2-955 DRY MOLY

MSDS Date:03/17/1988

FSC:9150

NIIN:00-827-5488

MSDS Number: BMQGT

=== Responsible Party ===

Company Name:CHEMICAL PACKAGING CORP

Address:2700 SW 14 ST

City:POMPANO BEACH

State:FL

ZIP:33069-4322

Country:US

Info Phone Num:305-874-5440

Emergency Phone Num:305-874-5440

CAGE:57040

=== Contractor Identification ===

Company Name:CHEMICAL PACKAGING CORP

Address:2700 SW 14 ST

Box:City:POMPANO BEACH

State:FL

ZIP:33069-4322

Country:US

Phone:305-974-5440

CAGE:57040

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Other REC Limits:NONE SPECIFIED

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450 STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemi

cal:1

Ingred Name:ACRYLIC COPOLYMER
Other REC Limits:NONE SPECIFIED

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TREATED CLAY
CAS:71011-27-3
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO
OSHA:NO

Health Hazards Acute and Chronic:INHALATION-MINIMAL EFFECTS BELOW 1,000 PPM; IRRITATION AT LEVELS ABOVE 1,000 PPM. PROLONGED SKIN CONTACT CAN CAUSE IRRITATION, DEFATTING OF THE SKIN AND DERMATITIS.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:INHALATION-DIZZINESS, DROWSINESS AND THROAT IRRITATION AT LEVELS ABOVE 1000 PPM. UNCONSCIOUSNESS AND DEATH

POSSIBLE AT LEVELS ABOVE 10,000 PPM.

Medical Cond Aggravated by Exposure:BLOOD PRESSURE, DEPRESSION, CARDIAC SENSITIZATION AND VENTRICULAR ARRHYTHMIA CAN RESULT FROM EXPOSURE TO NEAR-ANESTHETIC LEVELS.

===== First Aid Measures =====

First Aid:IF INHALED MOVE TO FRESH AIR. IF BREATHING HAS STOPPED ADMINISTER CPR. CALL A PHYSICIAN. UPON EYE CONTACT, FLUSH EYES IMMEDIATELY WITH WATER. IF IRRITATION PERSISTS, CALL PHYSICIAN. IF

INGESTED DO NOT INDUCE VOMITING. CALL PHYSICIAN. FOR SKIN CONTACT,
WASH AREA WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:56.0F,13.3C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CONCENTRATED VAPORS CAN BE IGNITED BY
HIGH INTENSITY ENERGY SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP AREA BY MOPPING OR WITH ABSORBENT
MATERIAL AND PLACE IN CLOSED CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN TIGHTLY SEALED, LABELS
CONTAINERS IN A COOL, DRY, WELL-VENTILATED AREA. PREVENT WATER
FROM ENTERING CONTAINERS.

Other Precautions:DO NOT ALLOW TO CONTACT WITH ALUMINUM. VAPOR HEAVIER
THAN AIR MAY COLLECT IN LOW AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED ORGANIC VAPOR TYPE RESPIRATOR
ACCEPTABLE IF CONCENTRATIONS 350-1000 PPM.

Ventilation:DO NOT USE IN CONFINED SPACES. OPEN DOOR &/OR WINDOWS.
MAINTAIN VAPOR BELOW 350 PPM.

Protective Gloves:CON. POLYVINYL ALCOHOL OR EQUAL.

Eye Protection:SAFETY GLASSES - CHEMICAL SPLASH GOGGLES

Other Protective Equipment:HAVE EMERGENCY EYE WASH AND SAFETY SHOWER
AVAILABLE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:105F,41C

Spec Gravity:1.3000

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID-MILDLY SWEET ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ALKALIES, OXIDIZERS, ALUMINUM AND O

OTHER REACTIVE METALS.

Stability Condition to Avoid: AVOID CONTACT WITH OPEN FLAMES, ELECTRIC ARC OR HOT SURFACES WHICH CAN CAUSE THERMAL DECOMPOSITION.

Hazardous Decomposition Products: HYDROGEN CHLORIDE, PHOSGENE (SMALL AMOUNTS).

===== Disposal Considerations =====

Waste Disposal Methods: MUST BE DISPOSED OF IN A PERMITTED WASTE MANAGEMENT FACILITY. CONSULT FEDERAL, STATE AND LOCAL DISPOSAL AUTHORITIES FOR APPROVED PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.