

POLYMERIC SYSTEMS, INC. -- PSI-690 PRIMER -- 8040-00-877-9872

=====  
Product Identification  
=====

Product ID:PSI-690 PRIMER

MSDS Date:12/14/1990

FSC:8040

NIIN:00-877-9872

Kit Part:Y

MSDS Number: BMQHM

=== Responsible Party ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:WHEATLAND & MASON STREETS

City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Info Phone Num:215-935-1170

Emergency Phone Num:215-93

5-1170

Preparer's Name:E F CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHANOL

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 90%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Name:METHANOL

CAS:67-56-1

RTECS #:PC1400000

Fraction by

Wt: 4%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:S,200PPM/250STEL  
ACGIH TLV:S,200PPM/250STEL; 93  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL POLYSILICATE  
CAS:68412-37-3  
Fraction by Wt: 2-4%  
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 6.5 LBS/GAL; 780 GRAMS/LITER  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO  
IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: MUCOUS MEMBRANE IRRITATION,  
DROWSINESS, PROSTRATION, NARCOSIS; SKIN IRRITATION; EYE IRRITATION.  
CHRONIC: DAMAGE TO LIVER, KIDNEY AND PERIPHERAL & OPTIC  
NERVE-JAUNDICE, EDEMA AND LOSS OF VISION.  
Effects of Overexposure:IRRITATION OF MUCOUS MEMBRANES, HEADACHE,  
DROWSINESS, FATIGUE, NARCOSIS.  
Medical Cond Aggravated by Exposure:EYE, SKIN AND RESPIRATORY DISORDERS  
AND IMPAIRED LIVER, KIDNEY AND OPTIC & PERIPHERAL NERVE FUNCT  
IONS  
MAY BE AGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====  
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS  
DIFFICULT. SKIN: FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING.  
EYE: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.  
INGESTION: DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR DROWSY.  
OTHERWISE, INDUCE VOMITING. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measu

res =====

Flash Point Method:CC

Flash Point:56.0F,13.3C

Autoignition Temp:Autoignition Temp Text:793F

Lower Limits:3.3

Upper Limits:19

Extinguishing Media:DRY CHEMICAL, FOAM, CO2, SAND, WATER SPRAY

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS OPERATED IN POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:SMOKE MAY CONTAIN HCL AS WELL AS NORMAL PARTIAL OXIDATION PRODUCTS OF HYDROCARBON COMBUSTION.

===== Accidental Release Measures ==

=====

Spill Release Procedures:TAKE UP WITH ABSORBENT MATERIAL. STORE IN APPROPRIATE CONTAINER. AVOID PROLONGED INHALATION OF VAPOR OR CONTACT WITH LIQUID. WASH RESIDUES WITH LARGE AMOUNTS OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID IGNITION SOURCES: FLAME, SPARKS, EXTREME HEAT. STORE IN WELL VENTILATED AREA.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED.

===== Exposure Controls/Person

al Protection =====

Respiratory Protection:IF LARGE AMOUNTS ARE USED IN A POORLY VENTILATED CLOSED SPACE, USE A CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE (NIOSH/MSHA APPROVED) TO PROTECT AGAINST ALCOHOL VAPORS.

Ventilation:LOCAL EXHAUST MAY BE REQUIRED IN CLOSED SPACES. RECOMMEND 10 CHANGES PER HOUR.

Protective Gloves:RUBBER OR POLYETHYLENE

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties ==

=====

Boiling Pt:B.P. Text:165F,74C  
Melt/Freeze Pt:M.P/F.P Text:-130F,-90C  
Decomp Temp:Decomp Text:>752F,>400C  
Vapor Pres:42  
Vapor Density:1.8  
Spec Gravity:0.80  
pH:7  
Viscosity:2 CPS @ 20C  
Evaporation Rate & Reference:1.4 (BU AC=1)  
Solubility in Water:98%  
Appearance and Odor:COLORLESS LIQUID, PLEASANT ODOR  
Percent Volatiles by Volume:95

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE  
Stability Condition to Avoid  
:OPEN FLAMES, SPARKS, EXTREME HEAT  
Hazardous Decomposition Products:BY COMBUSTION: CO, HCL, AEROSOLS OF  
SILICA & TITANIA, INCOMPLETE COMBUSTION PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH FEDERAL, STATE &  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of A  
merica in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.