

STOODY CO -- STELLITE "TM", SPECIFICATION AWS A5.13 A5.1 -- 3439-01-022-5848

===== Product Identification =====

Product ID:STELLITE "TM", SPECIFICATION AWS A5.13 A5.1

MSDS Date:09/04/1991

FSC:3439

NIIN:01-022-5848

MSDS Number: BMQKR

=== Responsible Party ===

Company Name:STOODY CO

Address:5557 NASHVILLE RD

Box:9997

City:BOWLING GREEN

State:KY

ZIP:42102-4997

Country:US

Info Phone Num:502-781-9777

E

mergency Phone Num:502-781-9777

CAGE:57965

=== Contractor Identification ===

Company Name:STOODY CO

Box:90032

City:BOWLING GREEN

State:KY

ZIP:42102-9032

Country:US

Phone:502-781-9777

CAGE:57965

===== Composition/Information on Ingredients =====

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 0-1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:(C) 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

Fraction

by Wt: 0-3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 5-35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 0-30%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #
:QA4680000
Fraction by Wt: 0-35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:TUNGSTEN
CAS:7440-33-7
RTECS #:YO7175000
Fraction by Wt: 0-15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3/ 10 STEL
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:VANADIUM (SARA III)
CAS:7440-62-2
RTECS #:YW1355000
Fracti

on by Wt: 0-2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:C,0.5 MG V2O5/M3 RD
ACGIH TLV:0.05 MG V205/M3;9293

Ingred Name:COBALT (SARA III)
CAS:7440-48-4
RTECS #:GF8750000
Fraction by Wt: 30-60%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MG/M3;AS CO
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:BORON
CAS:7440-42-8
RTECS #:ED7350000
Fraction by Wt: 0-3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 (AS OXIDE)
ACGIH TLV:10 MG/M3 (AS OXIDE)

===== Hazards Identification =====
=====

Routes of Entry: Inhalation:UNKNOWN Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ELECTRIC ARC WELDING OR OXY FUEL
WELDING MAY CREATE FUMES AND GASES WHICH CAN BE DANGEROUS TO YOUR
HEALTH. ACUTE: OVEREXPOSURE TO FUMES MAY RESULT IN DISCOMFORT SUCH
AS IRRITATION TO THE RESPIRATORY SYSTEM, DAMAGE TO LUNGS AND
ASTHMA-LIKESYMPTOMS, AND PULMONARY EDEMA BRONCHITIS. CHRONIC: CAN
LEAD TO SIDEROSIS.

E

xplanation of Carcinogenicity:CHROMIUM AND NICKEL AND THEIR COMPOUNDS
ARE ON THE IARC LIST AND NTP LIST AS POSING A CARCINOGENIC RISK TO
HUMANS.

Effects of Overexposure:CHROMATES PRESENT IN WELDING FUMES CAN CAUSE
ASTHMA-LIKE FUMES. NICKEL COMPOUNDS IN THE FUME CAN CAUSE A
METALLIC TASTE, NAUSEA, TIGHTNESS IN THE CHEST, FEVER AND ALLERGIC
REACTIONS. FLUORIDES MAY CAU SE A SKIN RASH.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====

First Aid Measures =====

First Aid:CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUES
RECOMMENDED BY THE AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE

Extinguishing Media:AS APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS
AND THE PRECAUTIONARY LABEL ON THE PRODUCT. SEE AMERICAN NATIONAL
STANDARD Z49.1, SAFETY IN WELDING AND CUTTING PUBLISHED BY THE
AMERICAN WELDING SOCIETY AND OSHA PUBLICATION 2206.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:

USE RESPIRABLE FUME RESPIRATOR OR AIR-SUPPLIED
RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:USE ENOUGH VENTILATION, LOCAL EXHAUST AT THE ARC, OR BOTH,
TO KEEP THE FUMES AND GASES BELOW TLV'S IN THE WORKER'S

Protective Gloves:WEAR PROTECTION TO PREVENT INJURY

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:ARM PROTECTORS, APRONS, HATS, SHOULDER
PROTECTION, AS
WELL AS DARK SUBSTANTIAL CLOTHING.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:NOT SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous

s Decomposition Products:GASEOUS REACTION PRODUCTS MAY INCLUDE
CARBON MONOXIDE AND CARBON DIOXIDE. OZONE AND NITROGEN OXIDES MAY
BE FORMED BY ARC

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR
LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE
WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.