

LOCTITE CORP -- GENERAL PURPOSE 53 EPOXY, 45381

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-062-3183
MSDS Date: 05/31/1991
MSDS Num: BMQMC
Product ID: GENERAL PURPOSE 53 EPOXY, 45381
MFN: 01
Responsible Party
Cage: 7K128
Name: LOCTITE CORP
Address: 705 NORTH MOUNTAIN RD
City: NEWINGTON CT 06
111
Info Phone Number: 203-278-1280
Emergency Phone Number: 203-278-1280
Preparer's Name: STEPHEN REPETTO
Published: Y

=====
Contractor Summary
=====

Cage: 7K128
Name: LOCTITE CORP
Address: 705 N MT RD
City: NEWINGTON CT 06111
Phone: 312-689-6200
Cage: 05972
Name: LOCTITE CORPORATION
Address: 1001 TROUT BROOK CROSSING
City: ROCKY HILL CT 06067-3910
Phone: 860-571-5100

=====
Item Description Information
=====

Item Name: EPOXY
=====

Ingredients
=====

Cas: 25068-38-6
RTECS #: KC2100000
Name: EPOXY RESIN
% Wt: 85-90

Cas: 108-95-2
RTECS #: SJ3325000
Name: PHENOL. LEL: 1.8%. UL: 8.6%
% Wt: 3-5
OSHA PEL: 5 PPM, S
ACGIH TLV: 5 PPM, S
EPA Rpt Qty: 1000 LBS
DOT Rpt Qt

y: 1000 LBS

Cas: 69-72-7
RTECS #: VO0525000
Name: SALICYLIC ACID
% Wt: 1-3

Cas: 112945-52-5
RTECS #: VV7310000
Name: SILICA, AMORPHOUS FUMED
% Wt: 1-3
OSHA PEL: 6 MG/M3
ACGIH TLV: 10 MG/M3 TDUST

Cas: 107-21-1
RTECS #: KW2975000
Name: ETHYLENE GLYCOL. LEL:3.2%. UL: 15.3
% Wt: 0.1-1
OSHA PEL: 50 PPM, C
ACGIH TLV: 50 PPM,VAPOR, C
EPA Rpt Qty: 1 LB
DOT Rpt Qty: 1 LB

Cas: 68410-23-1
Name: POLYAMIDE RESIN
% Wt: 85-90

Cas: 112-24-3
Name: TRIETHYLENE TETRAMINE
% Wt: 10-15

Cas: 90-72-2
RTECS #: SN3500000
Name: 2,4,6-TRIS(DIMETHYLAMINO METHYL) PHENOL
% Wt: 0.1-1
=====

Health Hazards Data
=====

LD50 LC50 Mixture: LD50:(ORAL,RAT)5000 MG/KG
Route Of Entry Inds - Inhalation: NO
Skin: NO
Ingestion: NO
Carcinogenicity I

nds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: SKIN/EYE IRRITANT. MAY CAUSE DERMATITIS ON PROLONGED CONTACT IN SENSITIVE INDIVIDUALS.

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: NONE KNOWN.

First Aid: INGEST:INDUCE VOMIT. OBTAIN MED ATTN. INHAL:REMOVE TO FRESH AIR. SUPPORT BRTHG. (GIVE O*2/ARTF RESP) (FP N). SKIN: FLUSH WITH WATER. EYE: FLUSH WITH WATER FOR AT LEAST 15 MIN. OBTAIN MED ATTN

=====
Handling and Disposal
=====

Spill Release Procedures: SOAK UP IN AN INERT ABSORBENT. STORE IN A PARTLY FILLED, CLOSED CONTAINER UNTIL DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE FOLLOWING EPA LOCAL, FEDERAL AND STATE REGULATIONS.

Handling And Storage Precautions: KEEP AWAY FROM EYES. AVOID SKIN CONTACT. STORE BELOW 110F TO PRESERVE SHELF LIFE.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 200F,93C

Lower Limits: SEE ING 2&5

Upper Limits: SEE ING 2&5

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosio

n Hazard: NONE.

=====
Control Measures
=====

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N).

Ventilation: NONE NORMALLY NEEDED.

Protective Gloves: RUBBER/PLASTIC GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES (FP N).

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplement

al Safety and Health: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

HCC: T6

B.P. Text: 300F,149C

Vapor Pres: <5@80F

Spec Gravity: 1

Solubility in Water: SLIGHT

Appearance and Odor: RESIN:BLUE. HARDENER:YELLOW. MILD ODOR.

Reactivity Data

Stability Indicator

: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: NONE KNOWN.

Hazardous Decomposition Products: NONE KNOWN.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 7K128

Trans ID NO: 104371

Product ID: GENERAL PURPOSE 53 EPOXY, 45381

MSDS Prepared Date: 05/31/1991

Review Date: 04/28/1992

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Additional Data: NOT REGULATED FOR TRANSPORTATION

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THI

S MODE OF TRANSPORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
HAZCOM Label
=====

Product ID: GENERAL PURPOSE 53 EPOXY, 45381

Cage: 7K128

Company Name: LOCTITE CORP

Street: 705 N MT RD

City: NEWINGTON CT

Zipcode: 06111

Health Emergency Phone: 203-278-1
280

Label Required IND: Y

Date Of Label Review: 01/31/1992

Status Code: C

Label Date: 01/31/1992

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. KEEP AWAY FROM HEAT AND FLAME. ACUTE:
CAUSES EYE AND SKIN IRRITATION. MAY CAUSE DERMATITIS ON PROLONGED CONTACT IN
SENSITIVE INDIVIDUALS. HEALTH HAZARD

S: NONE LISTED BY MANUFACTURER.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or perso

ns contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.