View NSN Online: https://aerobasegroup.kr/nsn/9150-00-188-9865

DELTA PETROLEUM CO., INC -- OE/HDO-50, MIL-L-2104C -- 9150-00-188-9865

Product ID:OE/HDO-50, MIL-L-2104C MSDS Date:10/09/1990 FSC:9150 NIIN:00-188-9865 MSDS Number: BMQRW === Responsible Party === Company Name: DELTA PETROLEUM CO., INC Box:10397 City: JEFFERSON State:LA ZIP:70181-0397 Country:US Info Phone Num:504-833-2861 Emergency Phone Num:504-833-2861 CAGE:7A34 8 === Contractor Identification === Company Name: DELTA PETROLEUM CO., INC Address:10352 RIVER ROAD, Box:10397 City:ST. ROSE State:LA ZIP:70087 Country:US Phone:504-832-2732 **CAGE:7A348** Ingred Name: HYDROTREATED BRIGHT STOCK BASED LUBRICATING OIL CAS:72623-83-7 Fraction by Wt: 51-56% Other REC Limits:NONE SPECIFIED Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC CAS:64742-65-0 RTECS #:PY8038

500 Fraction by Wt: 33-43% Other REC Limits:NONE SPECIFIED ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ZINC DIALKYLDITHIOPHOSPHATE & ZINC DIARYLDITHIOPHOSPHATE (MIXED) CAS:68649-42-3 Fraction by Wt: 5 G/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION, EYES AND SKIN: BELIEVED TO BE MINIMALLY IRRITATING. Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by E xposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: AS WITH MOST FOREIGN MATERIALS, SHOULD EYE CONTACT OCCUR, FLUSH EYES WITH PLENTY OF WATER. SKIN, INGESTION, AND INHALATION: NONE CONSIDERED NECESSARY.

Flash Point Method:COC

Flash Point:450F,232C

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, OR CARBON DIOXIDE.

Fire Fighting

Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO COOL FIRE EXPOSED CONTAINERS. USE WATER SPRAY TO DISPERSE THE VAPORS AND TO PROVIDE PROTECTION TO PERSONNEL. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. Neutralizing Agent:NONE

Handling and St

orage Precautions: MINIMUM FEASIBLE HANDLING TEMPERATURES SHOULD BE MAINTAINED. PERIODS OR EXPOSURE TO HIGH TEMPERATURES SHOULD BE MINIMIZED. Other Precautions: AVOID WATER CONTAMINATION. Respiratory Protection: NONE NORMALLY REQUIRED. Ventilation:NORMAL Protective Gloves:RECOMMENDED Eye Protection:SAFETY GLASSES. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: WASH HANDS THOROUGHLY AFTE **R HANDLING THIS** PRODUCT. Supplemental Safety and Health NONE HCC:V6 Spec Gravity:0.900 Viscosity:19.2 CST Appearance and Odor:BRIGHT AND CLEAR. Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND KETONES, COMBUSTION PRODUCTS OF NITROGEN AND SULFUR. 

Waste Disposal Methods:UNDER RCRA, IT IS THE RESPONSIBILITY OF THE USER OF PRODUCTS TO DETERMINE, AT THE TIME OF DISPOSAL, WHETHER PRODUCT MEETS RCRA CRITERIA FOR HAZARDOUS WASTE. FOLLOW ALL APPLICABLE LOCAL, STATE AND FEDE RAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated f

or use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.