View NSN Online: https://aerobasegroup.kr/nsn/5970-00-901-5331

Product ID:RED GLPT VARNISH 10-9002, 10-9003, 10-9008 MSDS Date:01/01/1987 FSC:5970 NIIN:00-901-5331 MSDS Number: BMQTD === Responsible Party === Company Name: G. C. ELECTRONICS Address:1801 MORGAN ST Box:1209 City:ROCKFORD State:IL ZIP:61105-1209 Country:US Info Phone Num:815-968-9661 Emergency Phone Num:815-968-9661 CAGE:80112 === Contractor Identification === Company Name: G. C. ELECTRONICS Address:1801 MORGAN ST Box:1209 City:ROCKFORD State:IL ZIP:61105-1209 Country:US Phone:815-968-9661 CAGE:80112 Company Name: WALLACE-MURRAY CORP, GC ELECTRONICS AUDIOTEX DIV Address:400 S WYMAN ST Box:City:ROCKFORD State:IL ZIP:61101-1314 Country:US CAGE:15202

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:13

30-20-7 RTECS #:ZE2100000 Fraction by Wt: 62% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PIGMENT (IRON OXIDE CAS 8011-97-0) Fraction by Wt: 36% Other REC Limits:NONE SPECIFIED

Ingred Name:AKLYD RESIN CAS:68459-31-4 Fraction by Wt: 2% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Repo rts of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:VAPORS CAUSE IRRITATION OF EYES, NOSE & THROAT. IN HIGH CONCENTRATIONS VAPORS ARE ANESTHETIC. Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure:VAPORS MAY CAUSE NAUSEA, HEADACHE AND VOMITING. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:REMOVE TO FRESH AIR, FLUSH SKIN AND EYES WITH WATER. IF DIFFICULTY BREATHING, GET MEDICAL ATTENTION AT ONCE. IF SWALLOWED, DO NOT INDUCE VOMITING AND GET MEDICAL ATTENTION IMMEDIATELY.

Flash Point Method:COC Flash Point:82.0F,27.8C Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. Unusual Fire/

Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
======================================
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION AND CLEAN UP WITH AN ABSORBENT MATERIAL.
======================================
Handling and Storage Precautions:KEEP CONTAINERS CLOSED .KEEP AWAY FROM IGNITION SOURCES. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR CONTACT WITH SKIN. Other Precautions:NONE
<pre>======== Exp osure Controls/Personal Protection ====================================</pre>
 Respiratory Protection:IN HIGH CONCENTRATIONS AIR MASK MAY BE REQUIRED. Ventilation:LOCAL EXHAUST TO PROVIDE ADEQUATE VENTILATION. Protective Gloves:PLASTIC GLOVES Eye Protection:SAFETY GLASSES - CHEMICAL SPLASH GOGGLES Other Protective Equipment:HAVE EMERGENCY EYE WASH AND SAFETY SHOWER AVAILABLE. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health
===== Physical/Chemical Properties ====================================
HCC:F3 Boiling Pt:=140.6C, 285.F Vapor Pres:10 MMHG Vapor Density:3.7 AIR=1 Viscosity:65-85 Solubility in Water:NOT SOLUBLE Appearance and Odor:RED ENAMEL.
======================================
Stability Indicator/Materials to Avoid:YES NO Stability Condition to Avoid:WARM STORAGESOURCES OF IGNITION. Hazardous Decomposition Products:NO
======================================
Wa

ste Disposal Methods:INCINERATE. DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professi onal advice to verify and assume responsibility for the suitability of this information to their particular situation.