View NSN Online: https://aerobasegroup.kr/nsn/9150-01-012-7533

CHESAPEAKE ASSOCIATED ENTERPRISES INC -- OILDAG -- 9150-01-012-7533

Product ID:OILDAG MSDS Date:01/19/1988 FSC:9150 NIIN:01-012-7533 MSDS Number: BMQTQ === Responsible Party === Company Name: CHESAPEAKE ASSOCIATED ENTERPRISES INC Address: GREATER HARTFORD INDUSTRIAL CENTER Box:555 City:BEL ARI State:MD ZIP:21014 Country:US Info Phone Num:301-838-0260 **Emergency Phon** e Num:301-838-0260 CAGE:7R834 === Contractor Identification === Company Name: ACHESON COLLOIDS CO DIV OF ACHESON INDUSTRIES INC Address:1600 WASHINGTON AVE Box:611747 **City:PORT HURON** State:MI ZIP:48061-1747 Country:US Phone:800-255-3924 CAGE:70079 Company Name: CHESAPEAKE ASSOC. ENT. Address:22 NEWPORT DR Box:City:FOREST HILL State:MD ZIP:21050 Country:US Phone:410-838-0260 CAGE:7R834

Ingred Name:PETROLEUM OIL CAS:8002-05-9 RTE CS #:SE7175000 Fraction by Wt: 85% Other REC Limits:NONE SPECIFIED OSHA PEL:400 PPM ACGIH TLV:400 PPM

Ingred Name:GRAPHITE, NATURAL CAS:7782-42-5 RTECS #:MD9659600 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION-NO ACU TE EFFECTS EXPECTED WITHIN EXPOSURE LIMITS. INGESTION-CAM CAUSE GASTROINTESTINAL IRRITATION. EYE-MAY CAUSE TEMPORARY EYE IRRITATION. SKIN-REPEATED CONTACT CAN CAUSE IRRITATION & DERMA TITIS. Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure: INGESTION-CAN CAUSE NAUSEA, VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUF ACTURER.

First Aid:EYES: FLUSH EYEA WITH WATER AND SEEK MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INHALATION: IF AFFECTED, REMOVE TO FRESH AIR. INGESTION: KEEP INDIVIDU SL CALM AND SEEK MEDICAL ATTENTION IMMEDIATELY.

Flash Point Method:COC Flash Point:425F,218C Extinguishing Media:CARBON DIOXID

E, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: APPLY	ABSORBENTMATERIAL	AND TRANSFER TO
CONTAINER.		

Handling and Storage Precautions: AVOID PROLONGED INHALATION OF MISTS OR VAPORS.

Other Precautions:NONE

======= Exposure Controls/Personal Protecti

on ==============

Respiratory Protection:IF THE TLV OF THE PRODUCT IS EXCEEDED, A MECHANICAL OR SELF-CONTAINED BREATHING APPARATUS IS ADVISED.
Ventilation:PROVIDE SUFFICIENT MECHANICAL(GENERAL) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV'S.
Protective Gloves:WEAR PROTECTIVE GLOVES.
Eye Protection:SAFETY GLASSES - CHEMICAL SPLASH GOGGLES
Other Protective Equipment:NO SPECIAL EQUIPMENT NECESSARY UNDER NORMAL USE. EMERGENCY EYE WASH AND SAFETY SHOWER.
Work Hygienic Practices:WASH THOROU
GHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING.
Supplemental Safety and Health NONE

HCC:V6 Vapor Pres:0.10 Spec Gravity:0.98 Solubility in Water:NIL Appearance and Odor:BLACK FLUID, BLAND ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Pro

ducts:CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods:CONSULT WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for it

s use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.