

CHEMRAY COATING CORP -- ENAMEL ALKYD GLOSS STRATA BLUE 15045 -- 8010-00-298-2287
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS STRATA BLUE 15045

MSDS Date:02/09/1989

FSC:8010

NIIN:00-298-2287

MSDS Number: BMSMF

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergenc

y Phone Num:800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS 66

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 54%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:LEAD DRIER

Fraction by Wt: 1%

Other RE

C Limits:NONE SPECIFIED
ACGIH TLV:.05 MG/M3

Ingred Name:VOC: 416 LBS/GAL OR 499 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATION (OVER 1000 PPM) ARE IRRITATING TO THE EYE & RESPIRATORY TRACT. MAY CAUSE HEADACHES & DIZZINESS. PROLONG SKIN CONTACT IRRITATES.

=====
First Aid
Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS CALL A PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:103F,39C
Lower Limits:.9
Upper Limits:7.0
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. FOR ENCLOSED CONTAINERS USE WATER SPRAY. AVOID BREATHING VAPOR OR FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITE SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT(SAND,

EARTH) TO SPILL. VENTILATE
AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING
SEWERS & WATERWAYS BY DIKING. ADVISE AUTHORITIES IF IT HAS
ENTERED.

=====
===== Handling and Storage =====

Other Precautions:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING AND INHALING THE C ONTENTS MAY BE HARMFUL
OR FATAL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATORY IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM; MECHANICAL: EXPLOSION-
PROOF EQUIPMENT. USE ONLY WITH ADEQUATE VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SPLASH GOGGLES OR FACESHIELD

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER
CLOTHING TO AVOID REPEATED SK
IN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND KEEP
CONTAINER CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F,153C

Melt/Freeze Pt:M.P/F.P Text: