

ALLOY RODS CORP -- ATOM ARC COVERED LOW HYDROGEN ELECTRODES, 8 -- 3439-01-216-0696

=====
Product Identification
=====

Product ID:ATOM ARC COVERED LOW HYDROGEN ELECTRODES, 8

MSDS Date:04/04/1988

FSC:3439

NIIN:01-216-0696

MSDS Number: BMSRX

=== Responsible Party ===

Company Name:ALLOY RODS CORP

Address:WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Info Phone Num:717-637-8911

Emer

gency Phone Num:717-637-8911

CAGE:GO230

=== Contractor Identification ===

Company Name:ALLOY RODS CORP

Address:1500 KAREN LN

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Phone:717-637-8911

CAGE:GO230

Company Name:ESAB GROUP INC

Address:801 WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Phone:717-637-8911 OR 800-933-7070

CAGE:84021

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

OSHA PEL:10 MG/M3

ACGIH

TLV:5 MG/M3

Ingred Name:CHROMIUM

CAS:7440-47-3

RTECS #:GB4200000

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICIC ACID (H*2SIO*3), DISODIUM SALT; (SODIUM SILICATE)

CAS:6834-92-0

RTECS #:VV9275000

Ingred Name:CALCIUM CARBONATE

CAS:1317-65-3

RTECS #:EV9580000

OSHA PEL:15 MG/M3 TDUST;5RESP

ACGIH TLV:10 MG/M3 TDUST

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE).

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MANGANESE

CAS:7439-96-5

RTECS #:OO9275000

OSHA PEL:(C) 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3; 9293

Ingred Name:POTASSIUM SILICATE

CAS:1312-76-1

Ingred Name:CALCIUM FLUORIDE

CAS:7789-75-5

RTECS #:EW1760000

OSHA PEL:2.5 MG/M3 AS F

ACGIH TLV:2.5 MG/M3 AS F

Ingred Name:POTASSIUM AL

UMINUM SILICATE (FELDSPAR); (POTASSIUM
FELDSPAR)
CAS:68476-25-5

Ingred Name:ZIRCONIUM DIOXIDE; (ZIRCONIUM SILCATE)
CAS:7440-67-2
OSHA PEL:5MG/M3; 10 STEL (ZR)
ACGIH TLV:5MG/M3: 10 STEL (ZR)

Ingred Name:SUPP DATA: AS DARK SUBSTANTIAL CLOTHING.
RTECS #:9999999ZZ

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:FUMES & GASES CAN BE DANGEROUS TO YOUR
HEALTH. AGGRAVATION OF PRE-EXISTING RESPIRATORY OR ALLERGIC
CONDITIONS MAY OCCUR IN SOME WORKERS. ACUTE: OVEREXP TO WELDING
FUMES MAY RESULT IN DISCOMFORT SUCH A S: DIZZINESS, NAUSEA, OR
DRYNESS OR IRRITATION OF NOSE, THROAT, OR EYES. CHRONIC: MAY LEAD
TO SIDEROSIS(EFTS OF OVEREXP)
Explanation of Carcinogenicity:CHROMIUM: GROUP 1 (NTP, IARC).
Effects of Overexposure:HLTH HAZ: (IRON DEPOSITS IN LUNGS) & IS

BELIEVED BY SOME INVESTIGATORS TO AFFECT PULMONARY FUNCTION. ARC
RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK CAN KILL.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH POTABLE WATER FOR AT LEAST 15
MINUTES. SEE MD. . SKIN: FLUSH WITH COPIOUS AMOUNTS OF WATER. CALL
MD . INGEST: GET MD IMMEDIATELY . INHAL: REMOVE TO FRESH AIR.
SUPPORT BREATHI
NG (GIVE O*2/ARTF RESP). CALL FOR MEDICAL AID.
EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL
PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:WELDING, ARC AND SPARKS CAN IGNITE
COMBUSTIBLES.

=====
===== Accidental Release Measures ===

=====

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPRVD RESPIRABLE FUME RESP/AIR SUPPLIED RESP WHEN WELDING IN CONFINED SPACE/WHERE LOCAL EXHAUST/VENT DOES NOT KEEP EXPOS BELOW TLV

Ventilation:USE ENOUGH VENT, LOC EXHST AT ARC/BOTH TO KEEP FUMES & GASES BELOW TLV'S IN WORKERS BRTHG ZONE & GENL AREA.

Protective Gloves:WELDING GLOVES.

Eye Protection:WEAR HELMET/USE FACE SHIELD (SUPP DATA)

Other Protective Equipment:WEAR HEAD, HAND & BODY PROTECTION WHICH HELP TO PREVENT INJURY FROM RADIATION SPARKS & ELECT SHOCK. AT MIN, (SUPP DATA)

Work Hygienic Practices:TRAIN WELDER TO KEEP HEAD OUT OF FUMES, NOT TO TOUCH LIVE ELCT PARTS & TO INSULATE HIMSELF FROM WORK & GROUND.

Supplemental Safety and Health

EYE PROT: WITH FILTER LENS. START W/A SHADE WHICH IS TOO DARK TO SEE WELD ZONE. THEN GO TO NEXT LIGHTER SHADE WHICH GIVES SUFFICIENT VIEW OF WELD ZONE. PROVIDE PROT SCREENS & FLASH GOGGS, IF NEC, TO S HIELD OTHERS. OTHER PROT: INCLUDES PROTFCSHLD & MAY INCLUDE ARM PROTS, APRONS, HATS, SHOULDER PROT, AS WELL (ING 13)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIE

D BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:FLUORIDES, COMPLEX OXIDES OF METALS LISTED IN INGREDIENTS, CO, CO*2, O*3, NO*X.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CNTNR, OR LINER IN AN ENVIRON ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE & LOCAL REG

UL ATIONS .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.