

CONOCO INTERNATIONAL INC -- GASOLINE, UNLEADED -- 9130-00-148-7103

===== Product Identification =====

Product ID:GASOLINE, UNLEADED

MSDS Date:10/08/1993

FSC:9130

NIIN:00-148-7103

MSDS Number: BMZQN

=== Responsible Party ===

Company Name:CONOCO INTERNATIONAL INC

Address:5 GREENWAY PLAZA EAST

Box:2197

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-293-5550

Emergency Phone Num:800-441

-3637/800-424-9300CHEM,TRANS

Preparer's Name:MSDS ADMINISTRATOR

CAGE:EO213

=== Contractor Identification ===

Company Name:CONOCO INC

Address:1000 S PINE

Box:1267

City:PONCA CITY

State:OK

ZIP:74603

Country:US

Phone:800-441-3637,CHEMTREC 800-424-9300

CAGE:58326

Company Name:CONOCO INC

Address:5 GREENWAY PLAZA E

Box:2197

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:713-293-5550PRODUCT/ 800-4413637MED

CAGE:5R396

Company Name:CONOCO INTERNATIONAL INC

Address:5 GREENWAY PLAZA EAST

Box:2197

City:HO

USTON
State:TX
ZIP:77001
Country:US
Phone:713-293-5550
CAGE:EO213
Company Name:MANASSAS ICE AND FUEL CO (MIFCO)
Address:9009 CENTER STREET
Box:City:MANASSAS
State:VA
ZIP:22110-5403
Country:US
Phone:703-368-3121
CAGE:2P282
Company Name:PAPCO OIL COMPANY LUBRICANTS
Address:4920 SOUTHERN BLVD.
Box:City:VIRGINIA BEACH
State:VA
ZIP:23462
Country:US
Phone:499-6977/872-0600
CAGE:2R096

=====
===== Composition/Information on Ingredients =====

Ingred Name:BENZENE (SARA III)
CAS:71-43-2
RTECS
#:CY1400000
Fraction by Wt: 0.1-4.9%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM/500 STEL
ACGIH TLV:300 PPM/500STEL;9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:GASOLINE (INCLUDING INGREDIENTS #1,2, 4 THRU 8)
CAS:8006-61-9
RTECS #:LX3300000
Fraction by Wt: 100

%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9293

Ingred Name:CUMENE (SARA III)
CAS:98-82-8
RTECS #:GR8575000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PSEUDOCUMENE (1,2,4-TRIMETHYLBENZENE) (SARA III)
CAS:95-63-6
RTECS #:DC3325000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9293

Ingred Name:XYLENES (O-, M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)
CAS:1634-04-4
RTECS #:KN52500

00

Fraction by Wt: 0-15%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:MAY CAUSE EYES, SKIN & LUNG IRRIT

AFTER PROLONGED/REPEATED EXPOSURE. EXTREME EXPOSURE/ASPIRATION INTO LUNGS MAY CAUSE LUNG DAMAGE OR DEATH. CHRONIC CONTA

CT MAY CAUSE

DERM. CONTAINS BENZENE WHICH MAY CAUSE LEUKEMIA & BE TOXIC TO BLOOD & BLOOD FORMING TISSUES. CONTAINS MTBE WHICH ODOR MAY CAUSE INDIGESTION & ABOVE SYMPTO

Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, LUNG

IRRITATION, WEAKNESS, HEADACHE, NAUSEA, VOMITING, CONFUSION, BLURRED VISION, DROWSINESS, DIZZINESS, SLURRED SPEECH, FLUSHE

D

FACE, UNCONSCIOUSNESS OR CONVULSIONS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.NOT BREATH GIVE ART RESP.DIFFICULTY BREATH GIVE OXYGEN.CALL DR.SKIN:WASH THOROUGHLY W/SOAP & WATER AFTER HANDLING.IRRIT DEVELOPS SEE DR.EYES:IMMED FLUSH W/PLENTY OF WATER FOR @ LEAST 15MINS.CALL DR.INGEST:DO NOT INDUCE VOMIT.IMMED GI

VE 2 GLASSES OF WATER.CALL A DR.ACTIVATED CHARCOAL MIXTURE (50G CHARCOAL/400ML WATER)MAY BE GIVEN.ADMINISTER 5ML/G OR 350ML FOR AVG ADULT.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-50F,-46C

Autoignition Temp:Autoignition Temp Text:536F

Lower Limits: 1

Spec Gravity:0.7-0.77

Solubility in Water:SLIGHTLY SOLUBLE.

Appearance and Odor:WATER WHITE TO STRAW YELLOW LIQUID, GASOLINE ODOR

Percent Volatiles by Volume:100 %

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

INCOMPATIBLE OR CAN REACT WITH STRONG OXIDIZERS.

Stability Condition to Avoid: AVOID UNDUE EXPOSURE TO AIR. AVOID HEAT, SPARKS AND FLAME.

Hazardous Decomposition Products: CARBON MONOXIDE MAY BE FORMED FROM INCOMPLETE COMBUSTION. ALSO CARBON DIOXIDE AND OTHER TOXIC MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods: TREATMENT/STORAGE /TRANSP/DISPOSAL MUST BE IAW

APPLICABLE LOC/STATE/FED REGS. DO NOT FLUSH TO SURFACE WATER OR SANITARY SEWER SYSTEM. BY ITSELF LIQ IS EXPECTED TO BE RCRA IGN HAZ WASTE. REPORT TO NAT RES P CNTR 800-424-8802 IF MATL ENTERS NAVIGABLE WATER

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.