View NSN Online: https://aerobasegroup.kr/nsn/6850-01-164-5738

NASHUA CORPORATION -- XEROX FUSER LUBRICANT FL-45,FL-75 -- 6850-01-164-5738

Product ID:XEROX FUSER LUBRICANT FL-45,FL-75

MSDS Date:06/28/1990

FSC:6850

NIIN:01-164-5738

MSDS Number: BMZZQ === Responsible Party ===

Company Name: NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA State:NH ZIP:03061 Country:US

Info Phone Num:800-258-1370 Emergency Phone Num:603

-880-5555

Preparer's Name: R.L. SEVIGNY

CAGE:0EK44

=== Contractor Identification ===

Company Name: NASHUA CORP OFFICE PRODUCTS DIV.

Address:44 FRANKLIN ST

Box:City:NASHUA

State:NH ZIP:03060 Country:US

Phone:603-880-2323

CAGE:34936

Company Name: NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA State:NH ZIP:03061 Country:US

Phone:603-880-5555

CAGE:0EK44

====== Composition/Information on Ingredients ========

Ingred Name: POLYDIMETHYLSILOXANE

CAS:63148-62-9 RTECS #:JT6485000

Fra

========== Hazards Identification ===========
Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO KNOWN CHRONIC OR CACUTE HAZARDS WHEN USED AS INTENDED. Explanation of Carcinogenicity:NOT RELAVENT Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES;HAS A LAXATIVE EFFECT UPON INGESTION. Medical Cond Aggravated by Exposure:NONE KNOWN
TO MFR
======================================
First Aid:SKIN:WASH WITH SOAP & WATER. EYES:FLUSH EYES WITH WATER FOR 15 MINUTES,CALL A PHYSICIAN. INGESTED:DRINK WATER AND CALL POISON CONTROL CENTER.
======================================
Flash Point Method:OC Flash Point:600F/316C Extinguishing Media:WATERFOG,CO*2,DRY CHEMICAL,FOAM. Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS, PROTECTIVE CLOTHING. Unusual
Fire/Explosion Hazard:NONE KNOWN TO MFR.
========= Accidental Release Measures ==========
Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTROL SP[ILLAGE. Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER
======================================
Handling and Storage Precautions:AVOID RUBBING EYES WITH HANDS WHILE USING THIS MATERIAL.CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.
Other Precautions:CLEAN U

ction by Wt: 100.0%

P SPILLS COMPLETELY AS RESIDUE IS SLIPPERY. UPON EYE CONTACT, REMOVE AND CLEAN CONTECT LENSES PRIOR TO REUSE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NOT REQUIRED.

Ventilation: NONE REQUIRED.

Protective Gloves: NONE REQUIRED Eye Protection: SAFETY GLASSES.

Other Protective Equipment: NONE REQUIRED.

Work Hygienic Practices: USE GOOD INDUSTRIAL HYGIENE PRACTICE. WASH

AFTER USING THE PRODUCT AND BEFORE EATING, DRINKING, ETC.

Supplemental Saf

ety and Health

MSDS RECEIVED FROM NAVY (FOCAL POINT N). NAVY IDENTIFIED NSN.

======== Physical/Chemical Properties ===========

HCC:N1 Boiling Pt:B.P. Text:>600F/316C Vapor Pres: