

R.H.CARLSON COMPANY,INC. -- NORSIL RTV 138 -- 8040-01-331-8046

=====
Product Identification
=====

Product ID:NORSIL RTV 138

MSDS Date:01/01/1987

FSC:8040

NIIN:01-331-8046

MSDS Number: BNCNK

=== Responsible Party ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41 CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Info Phone Num:203-531-5500

Emergency Phone Num:203-531-5500/800-424-9300

CHEMTREC

Preparer's Name:W J BUCHLER

CAGE:33530

=== Contractor Identification ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

=====
Composition/Information on Ingredients
=====

Ingred Name:ALTHOUGH THIS COMPOUND CONTAINS NO HAZARDOUS INGREDIENTS AS
RECOGNIZED AT THIS TIME, COMBINATION IN MIXTURE CAN

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

Ingred Nam

e: CONTRIBUTE TO CONDITIONS NORMALLY ASSOCIATED W/ADHESIVES.
PLEASE OBSERVE PROPER HYGIENE & HANDLING PROCEDURES AS
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

Ingrid Name:DESCRIBED IN THIS MSDS, TO PREVENT UNSAFE PRACTICES FROM
DEVELOPING OR OCCURRING.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:WARNING! MAY CAUSE IRRITATION. AVOID
CONTACT WITH SKIN, EYES AND CLOTHING,
DIRECT CONTACT WITH UNCURED
PRODUCT OR ITS VAPORS MAY CAUSE SLIGHT IRRITATION. INHALATION OF
THE VAPOR MAY PRODUCE RESPIRATOR Y IRRITATION. INGESTION OF THE
MATERIALMAY PRODUCE ABDOMINAL PAIN AND DIARRHEA.
Explanation of Carcinogenicity:NO INFORMATION FOUND.

=====
First Aid Measures
=====

First Aid:INGEST: DON'T INDUCE VOMIT. IF OCCURS, GIVE MORE FLUID. DR
DETERMINES WHETHER TO EVACUATE STOMACH/INDUCE VOMITING. DON'T GIVE
FLUIDS TO UNC
ONSCIOUS. SKIN: FLUSH W/WATER 15 MIN. REMOVE CONTAM
CLOTH/SHO ES. GET MED AID IF IRRIT OCCURS. WASH/DISCARD CLOTH. EYE:
IMMED FLUSH W/LRG AMT WATER 15 MIN. HOLD EYELIDS APART. DON'T
ATTEMPT TO NEUTRALIZE CHEM. GET MED AID ASAP. FLUSH 15 MIN MORE IF
NO MED AID.

=====
Fire Fighting Measures
=====

Fire Fighting Procedures:PREVENT EXPOSURE TO FIRE, SMOKE, FUMES,
COMBUST PRODUCTS. EVACUATE NON-ESSENTIAL. WEAR FULL FACE SCBA &
IMPERVIOUS PROT
ECT CLOTH. USE STD FIREFIGHT TECHNIQUES.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING & SPLASH GOGGLES.
SOAK UP LIQ W/ABSORBENT (SAWDUST, CLAY, OIL ABSORBER). SWEEP UP
ABSORBED MAT'L. PLACE IN CHEM WASTE DRUM. WASH UP AREA W/DETERGENT
& WATER. FLUSH W/ WATER. D IKE LRG SPILL & PUMP INTO DRUM
(SALVAGE/DISPOSAL).

=====
Handling and Storage
=====

Handling and Storage Preca

utions:AVOID CONTACT WITH SKIN & EYES, USE ONLY IN WELL VENTILATED AREA. CONTACT LENS WEARERS TAKE APPROPRIATE PRECAUTIONS. STORE IN A COOL PLACE.
Other Precautions:KEEP FROM HEAT, SPARKS AND FLAME. PRODUCT EVOLVES SLIGHT AMOUNTS OF ACETONE WHEN EXPOSED TO WATER OR HUMID AIR. OBSERVE LIMITS FOR ACETONE FORMED ON EXPOSURE TO WATER OR HUMID AIR, OSHA PEL AND ACGIH TLV 750 PPM.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF CONDITIONS GENERATE VAPOR, MATERIAL SHOULD BE HANDLED IN OPEN OR WELL-VENTILATED AREA. WHERE ADEQUATE VENT NOT AVAILABLE, USE NIOSH ORGANIC VAPOR RESPIRATOR. IN HIGH CONCENTRATION, POSITIVE PRESSURE AIR SUPPLY RSPRTR RECOMMENDED.
Ventilation:LOCAL EXHAUST IS REQUIRED AND GENERAL MECHANICAL VENTILTION IS SUGGESTED IN A CLOSED AREA.

Protective Gloves:APPROVED PLASTIC FILM/RUBBER GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:PROTECTIVE APRON OR COVERALLS.

Work Hygiene

Practices:FOLLOW GOOD INDUSTRIAL HYGIENE. KEEP AWAY FROM HEAT, SPARKS & FLAME. AVOID PROLONGED VAPOR BREATHING/CONTACT W/SKIN/EYES

Supplemental Safety and Health

(FIRST AID CONT'D) INHALATION: REMOVE FROM AREA. SEEK MEDICAL ATTENTION IF BREATHING IS DIFFICULT. OXYGEN MAY BE DELIVERED UPON A PHYSICIAN'S ADVICE. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH.

=====
===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:NEGLIGIBLE

GLIGIBLE

Vapor Density:>1

Spec Gravity:1.05

Viscosity:PASTE

Evaporation Rate & Reference:LESS THAN 1 (BU AC=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MILKY-WHITE OR CLEAR PASTE WITH SLIGHT ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL CAN CAUSE A REACTION, REACTS WITH ACIDS AND WATER, LIBERATING ACETONE.

Stability Condition to Avoid:EXPOSURE TO OXIDIZING MATERIAL UNTIL READY FOR USE.

Hazardous Decomposition Products: SILICONE DIOXIDE, CARBON DIOXIDE,
CARBON MONOXIDE, ACETONE.

===== Disposal Considerations =====

Waste Disposal Methods: MATERIAL THAT CANNOT BE USED SHOULD BE DISPOSED
OF IN AN EPA AUTHORIZED FACILITY. DISPOSE OF EMPTY CONTAINERS
ACCORDING TO ANY APPLICABLE REGULATIONS UNDER THE RESOURCE
CONSERVATION AND RECOVERY ACT.

Disclaimer (provided with this information by the compiling agencies):

This information is for
mulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.