

CROWN OIL AND CHEMICAL CO -- LUBRICATING OIL, MACHINE TOOL SLIDEWAYS

=====
MSDS Safety Information
=====

FSC: 9150
NIIN: 00-402-4480
MSDS Date: 06/24/1992
MSDS Num: BNKQL
Product ID: LUBRICATING OIL, MACHINE TOOL SLIDEWAYS
MFN: 01
Responsible Party
Cage: KO527
Name: CROWN OIL AND CHEMICAL CO
Address: 759 HILL ST.
Box: 106
92
City: JEFFERSON LA 70181
Info Phone Number: 504-733-9133
Emergency Phone Number: 800-424-9300 (CHEMTREC)
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: OCF76
Name: CROWN OIL & CHEMICAL CO.
Address: 751 HILL STREET
City: JEFFERSON LA 70121
Phone: 504 OUT OF BUSINESS
Cage: KO527
Name: CROWN OIL AND CHEMICAL COMPANY
Address: 751 HILL STREET
Box: 10692
City: JEFFERSON LA 70121
Phone: 504-733-9133
Cage: 4S446
Name: UNI-KEM INTERNATIONAL
Address: 1001 HARIMAW COURT EAST
City: METAIRIE LA 70001
Phone: 504-835-7600/FAX:504-835-7608

=====
Item Description Information
=====

Item Manager: S9G
Item Name: LUBRICATING OIL, MACHINE TOOL SLIDEWAY
Specification Number: MIL-L-46017
Type/Grade/Class: II TYPE
Unit of Issue: DR
Quantitative Expression: 00000000055

GL
UI Container Qty: 0
Type of Container: DRUM

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Effects of Exposure: PROLONGED OR REPEATED SKIN

CONTACT MAY CAUSE DERMATITIS

(SKIN IRRITATION).

Explanation Of Carcinogenicity: MANUFACTURER STATES THAT NO DATA AVAILABLE ON ACUTE TOXICOLOGICAL PROPERTIES.

Signs And Symptoms Of Overexposure: EYE-IRRITATION. SKIN-DRYNESS & IRRITATION.

Medical Cond Aggravated By Exposure: INDIVIDUALS WITH EXISTING SKIN DISEASES MAY BE AT INCREASED RISK.

First Aid: EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN. CONSULT A PHYSICIAN. SKIN-REMOVE EXCESS MATERIAL FROM SKIN WITH CLOTH OR P

APER.WASH

SKIN WITH SOAP & WATER. INGESTION: CONSULT PHYSICIAN IMM EDIATELY.

INHALATION OF OIL MIST OR FUMES, REMOVE TO FRESH AIR. CONTACT A PHYSICIAN IMMEDIATELY.

=====
Handling and Disposal
=====

Spill Release Procedures: TRANSFER BULK OF MIXTURE INTO ANOTHER CONTAINER.

ABSORB RESIDUE WITH INERT MATERIAL SUCH AS EARTH, SAND, OR VERMICULITE. SWEEP UP AND DISPOSE AS SOLID WASTE.

Neut

ralizing Agent: NONE STATED BY THE MANUFACTURER.

Waste Disposal Methods: CONSULT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: DO NOT HANDLE OR STORE AT TEMPERATURE OVER (MAXIMUM STORAGE TEMPERATURE) 38C.

Other Precautions: DO NOT CREATE MIST. DO NOT INHALE MIST OR VAPORS. IF WORKING WITH MIST OR FUMES, OBSERVE A TWA/PEL OF 5 MG/M3 FOR MINERAL OIL MIST (OSHA AND AGGIH). WASH THOROUGHLY

AFTER HANDLING.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: >400F,>204C

Extinguishing Media: DRY CHEMICAL OR WATER FOG OR CARBON DIOXIDE OR FOAM.
CLOSED CONTAINERS EXPOSED TO FIRE MAY BE COOLED WITH WATER.

Fire Fighting Procedures: DO NOT USE WATER EXCEPT AS FOG. CLOSED CONTAINERS
EXPOSED TO FIRE MAY BE COOLED WITH WATER.

Unusual Fire/Expl

losion Hazard: NONE STATED BY THE MANUFACTURER.
=====

Control Measures
=====

Respiratory Protection: USE NIOSH/MSHA CERTIFIED RESPIRATOR WITH ORGANIC VAPOR
CARTRIDGE IF VAPOR CONCENTRATION EXCEEDS PERMISSABLE EXPOSURE LIMIT.

Ventilation: USE LOCAL VENTILATION IF NECESSARY TO MAINTAIN ALLOWABLE PEL
(PERMISSIBLE EXPOSURE LIMITS OR TLV (THRESHOLD LIMIT VALUE.

Protective Gloves: NEOPRENE TYPE

Eye

Protection: CHEMICAL SAFETY GOGGLES

Other Protective Equipment: NONE STATED BY THE MANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER USING PRODUCT. DO NOT EAT, DRINK OR
SMOKE IN WORKING AREA.

Supplemental Safety and Health: NONE STATED BY THE MANUFACTURER.
=====

Physical/Chemical Properties
=====

HCC: V6

B.P. Text: >625F,>329C

M.P/F.P Text: <32F,<0C

Decomp Text: UNKNOWN

Vapor

Pres: 0

Solubility in Water: NEGLIGIBLE

Appearance and Odor: VISCOUS LIQUID, COLOR IS DARK GREEN-BROWN, ODOR IS BLAND.
=====

Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE GIVEN BY THE MANUFACTURER.

Materials To Avoid: STRONG OXIDIZERS SUCH AS HYDROGEN PEROXIDE, BROMINE, AND
CHROMIC ACID.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE FRO

M
BURNING.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NONE

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: KO527
Trans ID NO: 70751
Product ID: LUBRICATING OIL, MACHINE
TOOL SLIDEWAYS
MSDS Prepared Date: 06/24/1992
Review Date: 07/20/1992
MFN: 1
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: DR
Container QTY: 0
Type Of Container: DRUM
Additional Data: FREIGHT CLASSIFICATION: PETROLEUM LUBRICATING OIL.

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
HAZCOM Label
=====

Product ID: LUBRICATING OIL, MACHINE TOOL SLIDEWAYS

Cage: KO527

Assigned IND: Y

Company Name: CROWN OIL AND CHEMICAL COMPANY

Street: 751 HILL STREET

PO Box: 10692

City: JEFFERSON LA

Zipcode: 70121

Health Emergency Phone: 800-424

-9300 (CHEMTREC)

Date Of Label Review: 07/20/1992

Status Code: C

Label Date: 07/20/1992

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DERMATITIS
(SKIN IRRITATION). DO NOT HANDLE OR STORE AT TEMPERATURE OVER (MAXIMUM
STORAGE TEMPERATURE) 38C.

FIRST AID: EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN. CONSULT A PHYSICIAN. SKIN-REMOVE EXCESS MATERIAL FROM SKIN WITH CLOTH OR PAPER. WASH SKIN WITH SOAP & WATER. INGESTION: CONSULT PHYSICIAN IMMEDIATELY. INHALATION OF OIL MIST OR FUMES, REMOVE TO FRESH AIR. CONTACT A PHYSICIAN IMMEDIATELY.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United

States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.