View NSN Online: https://aerobasegroup.kr/nsn/6135-00-008-5341

Product ID:DISCHARGED BATTERY DRY CARBON-ZINC, MK105-0 MSDS Date:02/08/1991 FSC:6135 NIIN:00-008-5341 MSDS Number: BNMMB === Responsible Party === Company Name:NAVAL MINE WARFARE ENGINEERING ACTIVITY Address:CODE 60 BUILDING 1959 City:YORKTOWN State:VA ZIP:2 3691-5076 Country:US Info Phone Num:804-887-4930 Emergency Phone Num:804-887-4930 Preparer's Name: ANN ALLEN CAGE:30265 === Contractor Identification === Company Name: HOECHST CELANESE CHEM GROUP Box:City:DALLAS State:TX ZIP:75356-9320 Country:US Phone:214-689-4000 CAGE:10001 Company Name:NAVAL MINE WARFARE ENGINEERING ACTIVITY Address:CODE 60 BUILDING 1959 Box:City:YORKTOWN State:VA ZIP:23691-5076 Country:US Phone:804-887-4930 CAGE:30265

======= Composition/Information on Ingredients ===

Ingred Name:MERCURY CAS:7439-97-6 RTECS #:OV4550000 Fraction by Wt: 0.01% OSHA PEL:0.1 MG/M3, S, C ACGIH TLV:0.05 MG/M3, S EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ZINC CHLORIDE CAS:7646-85-7 RTECS #:ZH1400000 Fraction by Wt: 4.0% OSHA PEL:1 MG/M3/2 STEL ACGIH TLV:1 MG/M3/2STEL FUME93 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:AMMONIUM CHLORIDE CAS:12125-02-9 RTECS #:BP4550000 Fraction by Wt: 4.0% OSHA PEL:10MG/M3;20STEL, FUME ACGIH TLV:10MG/M3;20STEL, FUME EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE DIOXIDE CAS:1313-13-9 RTECS #:OP0350000 Fraction by Wt: 29.0% OSHA PEL:5 MG/M3 CEILING (MN) ACGIH TLV:5 MG/M3 (AS MN DUST)

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 11.0% OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3

Ingred Name:GRAPHITE CAS:7782-42-5 RTECS #:MD9659600 Other REC Limits:15 MPPCF (MFR) OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:MANGANESE CAS:7439-96-5 RTECS #:OO9275000 OSHA P EL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:AMMONIA CAS:7664-41-7 RTECS #:BO0875000 Other REC Limits:35 MG/M3 (MFR) OSHA PEL:50 PPM ACGIH TLV:25 PPM/35 STEL; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO I ngestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: IN FIRE SITUATION, CELLS MAY RELEASE HAZ SUBSTANCES. ACUTE: INHAL: MAY CAUSE IRRITATION OR METAL FUME FEVER IN FIRE SITUATION. INGEST: INGREDIENTS ARE POISONOUS. CONTACT: MATERIALS MAY CAUSE SKIN OR E YE IRRITATION BY VAPOR OR DIRECT CONTACT. CHRONIC: NOT LIKELY UNDER NORMAL USE. MANGANES & ZN CHLORIDE (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT. Effects of Over exposure:HLTH HAZ: ARE EXPERIMENTAL MUTAGENS & TUMOR PRODUCERS. ZN CHLORIDE IS AN EXPERIMENTAL TERATOGEN. Medical Cond Aggravated by Exposure: RESPIRATORY INFECTIONS AND DISEASES, SKIN DISEASES,

First Aid:INHAL:REMOVE TO FRESH AIR, USE ARTF RESP IF NEEDED. SEEK MED ATTN. EYES:FLUSH @ LST 15 MIN W/FRESH RUNNING H*20, OCCAS LIFTING UPPER & LOWER LID. SEEK MED ATTN. SKIN:THORO WASH AFFECTED AREA UNTIL NO TRAC E OF MATL REMAINS. INGEST:NOT LIKELY UNDER NORMAL USE. IF INGEST SHOULD OCCUR, GET IMMED MED ATTN. DRINK LG QTY OF H*20. EXPOS IN FIRE: REMOVE VICTIM FROM FIRE HAZ AREA TO FRESH AIR. SEEK MED ATTN. Flash Point:NOT KNOWN Extinguishing Media: IN BULK STORAGE USE CO*2, FOAM OR DRY POWDER. WATER MAY CAUSE ELECTRICAL SHORTS. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. Un usual Fire/Explosion Hazard: CELLS MAY RUPTURE WHEN EXPOSED TO EXCESSIVE HEAT. Spill Release Procedures: BATTERIES ARE DRY SOLID & CAN BE HNDLD EASILY W/SHOVELS/SIMILAR EQUIP. WHEN ACCUMULATING LG QTY OF UNDISCHARGED BATTERIES FOR DISP PACK IN NON-CONDUCTIVE INSULATING MATL. AVOID HEAT & H*2O. USE RUB GL OVES FOR CLEANING UP SPILLS/HNDLG (SUPPDATA) Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. ======== Handling and Storage Precautions: DO NOT STORE UNPACKAGED CELLS TOGETHER SO CONTACTS CAN TOUCH. THIS SITUATION WILL RESULT IN CELL SHORTING AND HEAT BUILD-UP. Other Precautions: DO NOT CHARGE, OVERHEAT (>160F), OR OPEN CELLS. AVOID CONTACT WITH WATER. Respiratory Protection: NONE NEEDED UNDER NORMAL USE. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN. Ventilation:NONE NEEDED. Protective Gloves: RUB GLOVES TO HNDLE INTERNAL COMPONENTS. Eye Protection: CHEM WORKERS GOGGLES IF CELLS OPENED. Other Protective Equipment: NONE REQUIRED UNDER NORMAL USE. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health HAZ DECOMP: ZINC CHLORIDE FUMES MAY BE EMITTED. SPILL PROC:INTERNAL PARTS OF CELLS. USE ADEQUATE VENTILATION AND AVOID CONTACT OF CELL INTERNAL COMPONENTS WITH SKIN OR EYES.

============

Boiling Pt:B.P. Text:>212F,>100C Vapor Density:>1 Spec Gravity:>1 Evaporation Rate & amp; Reference:>1(BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK SOLID GRANULES W/POSSIBLE AMMONIA ODOR, ENCASED IN BATTERY ASSEMBLY

Stability Indicator/Materials to Avoid:YES KEEP AWAY FROM WATER. Stability Condition to Avoid:EXCESSIVE HEAT AND FIRE (HEATI NG ABOVE 160F), CHARGING. Hazardous Decomposition Products:IN FIRE SITUATION, MERCURY VAP, AMMONIA CHLORIDE, AMMONIA, NITROUS OXIDES, CHLORINE, MANGANESE, ZINC OXIDE & (SUPP DATA)

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. DISPOSAL BY LANDFILL MAY BE ILLEGAL IN SOME AREAS.

Disclaimer (provided with this information by the compiling agencies): This info

rmation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.