

NONFLUID OIL CORP -- MIL-G-18709A -- 9150-00-526-4205

===== Product Identification =====

Product ID:MIL-G-18709A

MSDS Date:03/17/1992

FSC:9150

NIIN:00-526-4205

MSDS Number: BNMNM

=== Responsible Party ===

Company Name:NONFLUID OIL CORP

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Info Phone Num:201-344-3451

Emergency Phone Num:201-344-3451

CAGE:76736

=== Contractor Identi

fication ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (SEVERE)
HEAVY NAPHTHENIC

CAS:64742-52-5

RTECS #:PY8035001

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Ent

ry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT
TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN IRRITATION. EXPOSURES
TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION.
Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS MEMBRANES.

=====
===== First Aid Measures =====

First Aid:SKIN- WIPE OFF AND WASH WITH SOAP AND WATER. EYES- FLUSH

WITH COPIOUS AMOUNTS OF WATER AND SEE A DOCTOR. INHALATION- REMOVE
FROM EXPOSURE AREA TO FRESH AIR. INGESTION- ADMINISTER WATER AND
SEEK MEDICAL AID. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:375F,191C

Lower Limits:1

Upper Limits:6

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM AND WATER FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WITH
FACE SHIELD IN ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCE. RECOVER
FREE PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA.
SWEEP OR SCRAPE UP.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. HANDLE AND
STORE USING METHODS GENERALLY ADVOCATED FOR PETROLEUM PRODUCTS. DO

NOT STORE OR MIX WITH OXIDIZING MATERIALS.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:LOCAL EXHAUST RECOMMENDED TO CAPTURE HOT FUMES.

Protective Gloves:FOR PROLONGED OR FREQUENT CONTACT.

Eye Protection:RECOMMENDED IF SPLASHING OR MISTING.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR DRINKING. DO NOT
WEAR CONTAMINATED CLOTHING

TED CLOTHING. REMOVE AND LAUNDER BEFORE REUSE.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Melt/Freeze Pt:M.P/F.P Text:NEGLIGIBLE

Vapor Pres:10

Spec Gravity:0.91

Evaporation Rate & Reference: