

MG INDUSTRIES, WELDING PRODUCT DIVISION -- MG 500 -- 3439-00-027-0842

=====
Product Identification
=====

Product ID:MG 500

MSDS Date:08/01/1990

FSC:3439

NIIN:00-027-0842

MSDS Number: BNPKS

=== Responsible Party ===

Company Name:MG INDUSTRIES, WELDING PRODUCT DIVISION

Address:N94 W14335 GARWIN MACE DR

City:MENOMONEE FALLS

State:WI

ZIP:53051

Country:US

Info Phone Num:414-255-5520

Emergency Phone Nu

m:414-255-5520

CAGE:60097

=== Contractor Identification ===

Company Name:MG INDUSTRIES, WELDING PRODUCT DIVISION

Address:N94 W14335 GARWIN MACE DR

Box:City:MENOMONEE FALLS

State:WI

ZIP:53051

Country:US

Phone:414-255-5520

CAGE:60097

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Fraction by Wt: 65-75%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000
Fraction by Wt: 1-11%
Other REC Limits:NONE SPECIFIED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5-15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CELLULOSE (PAPER FIBER)
CAS:9004-34-6
RTECS #:FJ5691460
Fraction by Wt: 1-11%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9192

Ingred Name:SILICA GEL
CAS:1
12945-52-5
RTECS #:VV7310000
Fraction by Wt: 1-11%
Other REC Limits:NONE SPECIFIED
OSHA PEL:6 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:POTASSIUM SILICATE
CAS:1312-76-1
Fraction by Wt: 1-11%
Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM ALUMINUM SILICATE (FELDSPAR)
CAS:68476-25-5
Fraction by Wt: 1-11%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:2 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:NOT OTHERWISE CLASSIFIED IS 5 MG/M3
Route

s of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:FUMES AND GASES CAN BE DANGEROUS TO YOUR HEALTH. LONG-TERM (CHRONIC) OVEREXPOSURE MAY LEAD TO SIDEROSIS (IRON DEPOSITS IN THE LUNGS) AND IS BELIEVED BY SOME INVESTIGATORS TO AFFECT PULMONARY FUNCTION. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK CAN KILL.

Explanation of Carcinogenicity:NICKEL AND CHROMIUM ARE CONSIDERED CARCINOGENIC BY NTP AND IARC. ONLY CHROMIUM IS CONSIDERED CARCINOGENIC BY OSHA.

Effects of Overexposure:SHORT-TERM (ACUTE) OVEREXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS: DIZZINESS, NAUSEA, OR DRYNESS OR IRRITATION OF NOSE, THROAT OR EYES.

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY OR ALLERGIC CONDITION MAY BE ARRAGAVATED IN SOME INDIVIDUALS.

=====
===== First Aid Measures =====

First Aid:CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE
Extinguishing Media:NONE SPECIFIED BY MANUFACTURER.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard:WELDING ARC AND SPARKS CAN IGNITE COMBUSTIBLES. REFER TO AMERICAN NATIONAL STANDARD Z49.1 FOR FIRE PREVENTION DURING WELDING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS AND THE PRECAUTIONARY LABEL ON THIS PRODUCT. SEE AMERICAN NATIONAL STANDARD Z-49.1, SAFETY IN WELDING AND CUTTING, PUBLISHED BY THE AMERICAN WELDING SOCIETY, P.O. BOX 451040, MIAMI, FL.

=====
===== Exposure Controls/Personal

I Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIES
RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:USE ENOUGH VENTILATION, LOCAL EXHAUST AT THE ARC, OR BOTH
TO KEEP THE FUMES & GAESE BELOW THE TLV IN THE GENERAL AREA.

Protective Gloves:WELDOR'S GLOVES, ARM PROTECTORS.

Eye Protection:PROTECTIVE FACE SHIELD.

Other Protective Equipment:WEAR HEAD, HAND & BODY PROT
ECTION (APRONS,

HATS, SHOULDER PROTECTION, AS WELL AS DARK SUBSTANTIAL CLOTHING).

Work Hygienic Practices:TRAIN THE WELDER NOT TO TOUCH LIVE ELECTRICAL
PARTS AND TO INSULATE HIMSELF FROM WORK AND GROUND.

Supplemental Safety and Health

WELDING FUMES CANNOT BE CLASSIFIED SIMPLY. THE COMPOSITION AND QUANTITY
OF BOTH ARE DEPENDENT UPON THE MATERIAL BEING WELDED, THE PROCESS,
PROCEDURES AND ELECTRODES USED.

===== Physical/Chemical Properties =====

HCC:V7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:FUME CONSTITUENTS WOULD INCLUDE
COMPLEX OXIDES OF IRON, CHROMIUM, MANGANESE, SILICON, NICKEL &
MOLYBDENUM.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ANY GRINDING DUST OR WASTE RESIDUE IN
ACCORDANCE WITH EPA OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of th

is information to their particular situation.