View NSN Online: https://aerobasegroup.kr/nsn/6750-00-573-9241

EASTMAN KODAK COMPANY -- 160 8413 VERSAMAT 641 FIXER & REPLINISHER, PART A --

6750-00-573-9241

Product ID:160 8413 VERSAMAT 641 FIXER & REPLINISHER, PART A

MSDS Date:03/29/1995

FSC:6750

NIIN:00-573-9241

MSDS Number: BNQBK === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US Info Phone

Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Information on Ingredients

Ingred Name:SODIUM THIOSULFATE, PENTAHYDRATE

CAS:10102-17-7

RTECS #:WE6660000 Fraction by Wt: 80-85%

Other REC Limits: NONE SPECIFIED

Ingred Name:SODIUM ACETATE

CAS:126-96-5

RTECS #:AJ4375000 Fraction by Wt: 10-15%

Other REC Limits: NONE SPECIFIED

Ingred Name: SODIUM METABISULFITE

CAS:7681-57-4

RTECS #:UX8225000 Fraction by Wt: 5-10%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

Ingred Name: BORON OXIDE

CAS:1303-86-2

RTECS #:ED7900000 Fraction by Wt: 1-5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

============= Hazards Identification ========================

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: EXPECTED TO BE A LOW INHALATION HAZARD OF RECOMMENDED HANDLING. EYE CONTACT MAY CAUSE TRANSIENT EYE IRRITATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW INGESTION HA


ZARD.

Explanation of Carcinogenicity: NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure: EYE IRRITATION

Medical Cond Aggravated by Exposure: SUPPLIER DID NOT ADDRESS THIS FIELD.

First Aid:INHALED: IF SYMPTOMATIC, REMOVE TO FRESH AIR. EYE: ANYTHING THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. SKIN: WASH AFTER EACH CONTACT, INGESTED:



| ======= Physical/Chemical Properties =========== |
|--|
| HCC:N1 Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:NEGLIGIBLE Vapor Density:NOT GIVEN Spec Gravity:NOT GIVEN Evaporation Rate & DETERMINE SOLUBILE Solubility in Water:APPRECIABLE Appearance and Odor:WHITE POWDER; ODORLESS Percent Volatiles by Volume:NIL |
| ====================================== |
| Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, COMB USTIBLE MATERIAL, HALOGENATED MATERIALS, AQUEOUS AMMONIA. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF SULFUR. Conditions to Avoid Polymerization:WILL NOT OCCUR. |
| ========= Disposal Considerations ============== |
| Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH AL L FEDERAL, STATE AND LOCAL REGULATIONS. |
| Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and |

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.