

DOW CORNING CORP -- MOLYKOTE M GEAR GUARD -- 9150-01-344-2197
===== Product Identification =====

Product ID:MOLYKOTE M GEAR GUARD

MSDS Date:09/24/1985

FSC:9150

NIIN:01-344-2197

MSDS Number: BNRMD

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Preparer's Name:J

ACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENTS. (GREASE)

===== Hazar

ds Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:MAY CAUSE TEMPORARY DISCOMFORT.

SKIN:SINGLE, PRLNGD EXPOS (HOURS) CAUSES NO KNOWN EFT. SEVERAL

RPTD, PRLNGD EXPOS MAY CAUSE SLIGHT IRRIT. INHAL:NO EFTS EXCEPT

VERY SLIGHT IRRIT/PAIN TO EYES/RESP P ASSAGES. INGEST:AMOUNTS

TRANSFERRED TO THE MOUTH B

Y FINGERS, ETC,. DURING NORMAL OPERATIONS

SHOULD NOT (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:CAUSE INJURY. COMMENT:NO KNOWN ADVERSE

CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL

SHOULD BE AVOIDED. THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE

ALLERGIC CNDTNS ON C CERTAIN PEOPLE.

Medical Cond Aggravated by Exposure:WE DO NOT KNOWN OF ANY MD

CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WIPE OFF

AND FLUSH WITH WATER. INHAL: NO PROBLEM. REMOVE TO FRESH AIR.

SUPPORT BREATHING (GIVE O*2/ARTF RESP) . INGEST:NO PROBLEM. CALL MD

IMM ED .

===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>250F,121C

Extinguishing Media:WATER FOG, CO*2, DRY CHEMICAL, FOAM,

Fire Fighting Procedures:WEAR NI

OSH/MSHA APPROVED SCBA AND FULL

PROTECTIVE CLOTHING .

Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN

FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.

Other Precautions:PRECAUTION

S GIVEN ARE FOR ROOM TEMPERATURE HANDLING.

USE @ ELEVATED TEMPERATURES MAY REQUIRE ADDED PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED. NIOSH/MSHA APPROVED
RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST:NONE. MECH:RECOMMENDED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Pr

actices:GOOD PRAC REQ THAT GROSS AMT OF ANY CHEM BE

REMOVED FROM SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE (SUPP
DATA)

Supplemental Safety and Health

HYGIENE PRACT: EATING/SMOKING. WASHING @ MEALTIME & END OF WORKSHIFT IS
ADEQUATE. REMOVE CONTAMINATED CLOTHING AND SHOES @ END OF WORK &
CLEAN THOROUGHLY BEFORE REUSE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>300F,149C

Vapor Pres: