

DIAL CORP THE -- XEA 9396, PART A -- 8040-00-209-1286

===== Product Identification =====

Product ID:XEA 9396, PART A

MSDS Date:09/29/1989

FSC:8040

NIIN:00-209-1286

Kit Part:Y

MSDS Number: BNRND

=== Responsible Party ===

Company Name:DIAL CORP THE

Address:1865 DIAL TOWER

Box:312

City:PHOENIX

State:AZ

ZIP:85077-1865

Country:US

Info Phone Num:602-991-3000

Emergency Phone Num:602-991-3000

Preparer's

Name:SUZANNE FRANZ

CAGE:0EK45

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:DIAL CORP THE

Address:111 W CLARENDON AVE

Box:3223

City:PHOENIX

State:AZ

ZIP:85077

Country:US

Phone:602-991-3000

CAGE:0EK45

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN SYSTEM

Other REC Limits:NON

E SPECIFIED

Ingred Name:VOC: 300F,>149C

Extinguishing Media:DRY CHEMICAL, HALON FIRE EXTINGUISHER, WATER SPRAY, FOAM, OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT 40 F FOR 12 MONTHS. FOLLOW RECOMMENDED CURING SCHEDULE.

Other Precautions:AVOID CONTACT WITH EYES OR SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. DO NOT HANDLE OR USE UNTIL MSDS HAS BEEN READ AND UNDERSTOOD.

Supplemental Safety and Health

KEY1:T6. FAILURE TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT BUILDUP WITH THE RELEASE OF TOXIC GASES.

===== P

Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:BLUE PASTE WITH SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND
UNDETERMINED ORGANICS.

Conditions to Avoid Polymeriza

tion:AVOID MIXING RESIN/CURING AGENT IN

BATCHES >1 LB. DON'T HEAT MIXED ADHESIVE >125 F UNLESS CURING
SURFACES TO BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in

no manner whatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.