

CONSOLIDATED MOTOR OIL CO INC -- PETROLATUM,TECHNICAL -- 9150-00-250-0933

===== Product Identification =====

Product ID:PETROLATUM,TECHNICAL

MSDS Date:09/10/1992

FSC:9150

NIIN:00-250-0933

MSDS Number: BNRNN

=== Responsible Party ===

Company Name:CONSOLIDATED MOTOR OIL CO INC

Address:1773 PINE AVE

Box:427

City:VINELAND

State:NJ

ZIP:08360-3442

Country:US

Info Phone Num:609-691-1066

Emergency Phone

Num:609-691-1066

Preparer's Name:DGSC-SSH

CAGE:9Z316

=== Contractor Identification ===

Company Name:CONSOLIDATED MOTOR OIL CO INC

Address:1773 PINE AVE

Box:427

City:VINELAND

State:NJ

ZIP:08360-3442

Country:US

Phone:609-691-1066

CAGE:9Z316

===== Composition/Information on Ingredients =====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Other REC Limits: 5 MG/M3 OIL MIST

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES

Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- MAY CAUSE IRRITATION OF EYES, SKIN & G.I. TRACT. CNS EFFECTS LIKE HEADACHE, DIZZINESS, NAUSEA AND VOMITING POSSIBLE IF MATERIAL IS HEATED OR MISTS PRESENT AND INHALED. REDNESS AND/OR BURNS OF EYES/SKIN MAY OCCUR. CHRONIC: DRYING OF SKIN AND DEFATTING.

Effects of Overexposure:MAY CAUSE IRRITATION OF EYES, SKIN & G.I. TRACT. CNS EFFECTS LIKE HEADACHE, DIZZINESS, NAUSEA AND VOMITING

POSSIBLE IF MISTS OR VAPORS ARE PRESENT AND INHALED. REDNESS AND/OR BURNS OF EYES/SKIN MAY OC CUR.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE EXCESS. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR &

PROVIDE OXYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCE VOMITING.GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C

Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER FOG, SAND OR EARTH

Fire Fighting Procedures:WATER SPRAY IS AN UNSUITABLE EXTINGUISHING AGENT. FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST SMOKE INHALATION.

Unusual Fire/Explosion Hazard:DENSE SMOKE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. ABSORB RESIDUE WITH AN INERT MATERIAL SUCH AS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH APPROPRIATE CLEANER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE AWAY FROM FLAME, EXCESSIVE HEAT AND STRONG OXIDIZING AGENTS.

Other Precautions:AVOID BREATHING

VAPORS OR MISTS. DO NOT GET IN EYES,
ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT
OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:ROOM VENTILATION

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND
IMP

ERVIIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NO MSDS WAS AVAILABLE FROM MANUFACTURER. THIS MSDS WAS PREPARED BY THE
PROFESSIONALS OF DGSC-SSH WITHOUT ANY WARRANTY. IT IS THE USER'S
RESPONSIBILITY TO GATHER INFORMATION AND USE THE MATERIAL PROPER LY
TO PROTECT EMPLOYEES AND ENVIRONMENT.

=====
===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity: