

ANSUL FIRE PROTECTION, WORMALD U.S.INC. -- CARBON DIOXIDE -- 4210-00-134-8958  
===== Product Identification =====

Product ID:CARBON DIOXIDE  
MSDS Date:01/25/1993  
FSC:4210  
NIIN:00-134-8958  
MSDS Number: BNSXX  
=== Responsible Party ===  
Company Name:ANSUL FIRE PROTECTION, WORMALD U.S.INC.  
Address:ONE STANTON STREET  
City:MARINETTE  
State:WI  
ZIP:54143-2542  
Country:US  
Info Phone Num:715-735-7411...FAX 715-7  
32-3477  
Emergency Phone Num:715-735-7411...TOM LAWSON EXT 580  
CAGE:03670  
=== Contractor Identification ===  
Company Name:ANSUL INC  
Address:ONE STANTON STREET  
Box:City:MARINETTE  
State:WI  
ZIP:54143-2542  
Country:US  
Phone:715-735-7411  
CAGE:03670

===== Composition/Information on Ingredients =====

Ingred Name:CARBON DIOXIDE  
CAS:124-38-9  
RTECS #:FF6400000  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5000 PPM  
ACGIH TLV:5000PPM/30000STEL;94

===== Haza

Product Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-CONTACT WITH COLD VAPOR/SOLID CARBON DIOXIDE CAN CAUSE EYE/SKIN FROSTBITE AND FREEZE BURNS. ASPHYXIANT BY INHALATION & HEAVIER THAN AIR. CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE. BREATHING HIGH CONCENTRATIONS WILL CAUSE LIGHT

THEADEDNESS, SHORTNESS OF BREATH. INGESTION IS UNLIKELY. CHRONIC-UNKNOWN.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS BUT NO OTHER COMMENTS WERE RECORDED.

Effects of Overexposure:DIZZINESS, IMPAIRED COORDINATION, REDUCED MENTAL ACUITY, HEADACHES, TINNITUS, DIFFICULTY BREATHING, AND/OR DROWSINESS DEPENDING ON LENGTH OF EXPOSURE & CONCENTRATIONS.

Medical Condition Aggravated by Exposure:RESPIRATORY PROBLEMS

===== First Aid Measures =====

=====

First Aid:IF ANY IRRITATION PERSISTS OR SEVERE, GET MEDICAL ATTENTION. TREAT FOR FROSTBITE IF NECESSARY. EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. INHALED:REMOVE FROM CONTAMINATED AREA. IF SYMPTOMS OCCUR, CONSULT MEDICAL PERSONNEL. AIDOR RESTORE BREATHING AS NEEDED. INGESTED:MFR GAVE NO INFORMATION ON MSDS.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:THIS IS AN EXTINGUISHING AGENT. HM

IS:USE

EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:NONE - THIS IS AN EXTINGUISHING AGENT.

Unusual Fire/Explosion Hazard:THOUGH GAS CYLINDERS ARE EQUIPPED WITH PRESSURE AND TEMPERATURE RELIEF DEVICES, THEY SHOULD BE REMOVED FROM HIGH TEMPERATURES OR FIRE TO AVOID RISK OF RUPTURE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. VENTILATE TO OUTSIDE ATMOSPHERE. COOL OR REMOVE HOT, M

ETAL SURFACES OR SOURCE OF NON-  
EXTINGUISHED FLAMES.

Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A CEAN, DRY, WELL-VENTILATED  
AREA AWWAY FROM HEAT ABOVE 120F. STORE AS A COMPRESSED GAS IN DOT  
APPROVED VESSELS.

Other Precautions:IF NOT ATTACHED TO A SYSTEM, CYLINDER/CARTRIDGE MUST  
BE SAFETY CAPPED TO PROTECT AGAINST VIOLENT VELLEL MOVEMENT OR  
FORCE OF EXCAPIN  
G GAS IF VALVE IS ACTUATED OR SEAL IS PUNCTURED.  
NOTE INCOMPATIBILIT Y INFORMATION.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NORMALLY NECESSARY IF CONTROLS ARE ADEQUATE.  
IF TLV IS EXCEEDED OR IF EXPOSURE IS PROLONGED, A SELF-CONTAINED  
BREATHING APPARATUS IS RECOMMENDED.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS RECOMMENDED W/LOCAL  
EXHAUST RECOMMENDED FOR CONFINED SPACES.

Protective Gloves:FOR CONTACT W/DRY ICE

Eye Prot

ection:CHEMICAL GOGGLES + FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTHING FOR CONTACT W/DRY ICE.

Work Hygienic Practices:MFR:?. HMIS:USE GOOD CHEMICAL HYGIENE  
PRACTICES. AVOID CONTACT IF AT ALL POSSIBLE. WASH THOROUGHLY AFTER  
HANDLING.

Supplemental Safety and Health

NONE

=====  
Physical/Chemical Properties  
=====

HCC:G3

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:SUBLIMES

Vapor Pres:830 PSI

Vapor Density:1.5

Spec Gravity:1.98

Evaporation Rate & amp;

Reference:GAS AT ROOM TEMPERATURE  
Solubility in Water:88ML/100 ML  
Appearance and Odor:COLORLESS GAS W/NO ODOR  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
REACTS VIGOROUSLY W/(AL+NA2O2), CS2O, LI, K, MG(C2H5) 2, (MG+NA2O),  
KHC2, NA, NA2C2, NAK, TI  
Hazardous Decomposition Products:NONE  
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====  
=====

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their  
particular situation.