

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3100 (PART B) -- 8030-00-881-5238

=====
Product Identification
=====

Product ID:CS 3100 (PART B)

MSDS Date:03/16/1990

FSC:8030

NIIN:00-881-5238

Kit Part:Y

MSDS Number: BNTMD

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:818-982-1650

Emergency P

hone Num:800-424-9300 CHEMTREC

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD DIOXIDE

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 64%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.15 MG/M3

Ingred Name:LEAD OXIDE

CAS:1317-36-8

RTECS

#:OG1750000
Fraction by Wt: 6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.05 MG/M3
ACGIH TLV:0.15 MG/M3

Ingred Name:EXPOSURE LIMITS-BASED ON DUST PARTICLES. LEAD DIOXIDE/OXIDE
PARTICLES ARE WETTED OUT THEREFORE NO AIRBORNE PARTICLES.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: WEAKNESS, STUPOR. CHRONIC:
KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS.
Effects of Overexposure:HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR
DYSFUNCTION.
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

=====
===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING, CONSULT A PHYSICIAN AT ONCE. EYE
CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER AND CONTACT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash
Point:>200F,>93C
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS WITH
FULL FACE-PIECE, IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT WITH
OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

=====
===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL DRY AREA. KEEP CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF SOOT IS FORMED USE NIOSH APPROVED RESPIRATOR.
Ventilation:AIR HOOD, FAN.
Protective Gloves:RUBBER GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR DRINKING.
TRAIN PERSONNEL IN THE SAFE HANDLING OF THIS PRODUCT.
Supplemental Safety and Health
KEY1:D2.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:644F,340C
Melt/Freeze Pt:M.P/F.P Text:LIQ-RM TEMP
Vapor Pres:NIL
Spec Gravity:3.00
Evaporation Rate & Reference:NIL
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN PASTE; OILY ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZABLE MATERIALS.
Stability Condition to Avoid:HIGH HEAT.
Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH BASE AND DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.